



Lindy 5m DisplayPort 1.4 Cable, Anthra Line

Brand : Lindy

Product code: 36484

Product name : 5m DisplayPort 1.4 Cable, Anthra Line

5m DisplayPort 1.4 Cable, Anthra Line


[Lindy 5m DisplayPort 1.4 Cable, Anthra Line:](#)

From the Lines cable connectivity concept developed by Lindy, Anthra Line DisplayPort cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line DisplayPort cables are premium connections that feature triple shielded with 28AWG tinned copper conductors for performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@120Hz 4:2:2 8bit and HDCP are supported. DisplayPort 1.2 technology and DisplayPort compliance certification ensures compatibility with all DisplayPort enabled devices.

Anthra Line DisplayPort cables are available in lengths from 0.5m to 5m.



Features

Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
DisplayPort version	1.2
Maximum resolution *	4096 x 2160 pixels
Supported graphics resolutions	4096 x 2160
Supported video modes	2160p
Maximum refresh rate	120 Hz
Cable length *	5 m
Connector 1 *	DisplayPort
Connector 2 *	DisplayPort
Connector 1 gender *	Male
Connector 2 gender *	Male
Product colour *	Black, Grey
Cable material	Tinned copper
Cable shielding	Copper
Jacket material	Polyvinyl chloride (PVC)
Connector housing material	Acrylonitrile butadiene styrene (ABS)
AWG wire size	28
Data transfer rate	21.6 Gbit/s
Contact material	Phosphor bronze

Features

Connector material	Gold
Plug and Play	✓
Colour sampling	4:2:2
Cable type	Round cable
Nominal attenuation	100MHz-450MHz 5.1dB, 450MHz-8100MHz 33.28dB

Operational conditions

Operating temperature (T-T)	-20 - 80 °C
Storage temperature (T-T)	-25 - 85 °C

Certificates

Certification	RoHS, REACH, UL
---------------	-----------------

Weight & dimensions

Cable diameter	7.3 mm
Connector 1 dimensions (WxDxH)	21 x 38.9 x 13.6 mm
Connector 2 dimensions (WxDxH)	21 x 38.9 x 13.6 mm
Bend radius (min)	5.84 cm

Packaging data

Package type	Polybag
--------------	---------

Packaging content

Quantity per pack	1 pc(s)
-------------------	---------

Logistics data

Harmonized System (HS) code	84733080
-----------------------------	----------



4002888364843

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.