



## Lindy 2m DisplayPort 1.4 Cable, Cromo Line

**Brand :** Lindy

**Product code:** 36302

**Product name :** 2m DisplayPort 1.4 Cable, Cromo Line

2m DisplayPort 1.4 Cable, Cromo Line

[Lindy 2m DisplayPort 1.4 Cable, Cromo Line:](#)

From the Lines cable connectivity concept developed by Lindy, Cromo Line DisplayPort cables are high performance, designer connections that combine premium construction materials with striking connector architecture.

Cromo Line DisplayPort Cables feature triple shielded construction with 28AWG conductors for premium performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 8K 7680x4320@60Hz 4:2:2 8bit, including 4K 4096x2160@120Hz 8bit, are supported. Cromo Line DisplayPort cables are capable of delivering 4:4:4 colour spacing for the most accurate colour representation possible.

Cromo Line cables feature sleek chrome design ABS housing to complement the aesthetics of style focused commercial and home applications.

Cromo Line DisplayPort cables are available in lengths from 0.5m to 5m.



Features		Features	
Connector 1 form factor	Straight	Connector material	Gold
Connector 2 form factor	Straight	Colour sampling	4:2:2
Connector contacts plating	Gold	Cable type	Round cable
DisplayPort version	1.4		300kHz-825MHz
Maximum resolution *	7680 x 4320 pixels	Nominal attenuation	5dB,825MHz-2.475GHz
Supported graphics resolutions	7680 x 4320		5dB,2.475GHz-4.125GHz
Maximum refresh rate	60 Hz		12dB,4.125GHz-5.1GHz 20dB
Cable length *	2 m	<b>Operational conditions</b>	
Connector 1 *	DisplayPort	Operating temperature (T-T)	-20 - 80 °C
Connector 2 *	DisplayPort	Storage temperature (T-T)	-25 - 85 °C
Connector 1 gender *	Male	<b>Certificates</b>	
Connector 2 gender *	Male	Certification	RoHS, REACH, UL,
Product colour *	Grey	<b>Weight &amp; dimensions</b>	
Cable material	Tinned copper	Cable diameter	7.3 mm
Cable shielding	Copper	Connector 1 dimensions (WxDxH)	19.7 x 12 x 38.9 mm
Jacket material	Polyvinyl chloride (PVC)	Connector 2 dimensions (WxDxH)	19.7 x 12 x 38.9 mm
Connector housing material	Acrylonitrile butadiene styrene (ABS)	Bend radius (min)	7.3 cm
AWG wire size	28	<b>Packaging data</b>	
Data transfer rate	32.4 Gbit/s	Package type	Polybag
Contact material	Phosphor copper	<b>Logistics data</b>	
		Harmonized System (HS) code	84733080



4002888363020

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-FEB-2025. Prints or copies of Information are only valid on the printed Publication date