

Lindy 5m USB 3.2 Type A to B Cable, 5Gbps, Anthra Line

Brand : Lindy

Product code: 36744

Product name : 5m USB 3.2 Type A to B Cable, 5Gbps, Anthra Line

- Professional choice USB 3.2 Gen 1 Type A to B cable for commercial and high performance AV and IT installations

- SuperSpeed USB - supports data transfer speeds up to 5Gbps (USB 3.0, USB 3.1 Gen 1)

- Robust PVC housing, gold plated connectors and contacts

- Triple shielded cable, corrosion resistant tinned copper conductors

- 10 year warranty

5m USB 3.2 Type A to B Cable, 5Gbps, Anthra Line

Lindy 5m USB 3.2 Type A to B Cable, 5Gbps, Anthra Line. Cable length: 5 m. Connector 1: USB A, Connector 2: USB B, USB version: USB 3.2 Gen 1 (3.1 Gen 1), Maximum data transfer rate: 5 Gbit/s, Connector contacts plating: Gold, Product colour: Black



Features		Features	
USB version *	USB 3.2 Gen 1 (3.1 Gen 1)	Nominal attenuation	0.5-5m: 0.5MHz-7.5GHz25DB
Connector 1 *	USB A	Weight & dimensions	
Connector 2 * Connector 1 gender * Connector 2 gender * Connector 1 form factor Connector 2 form factor	nnector 1 gender * Male nnector 2 gender * Male nnector 2 gender * Male nnector 1 form factor Straight /G wire size 26/28 nnector material Gold ntact material Copper nnector contacts plating Gold ble jacket material Polyvinyl chloride (PVC) nductor material Aluminium nnector shield material Aluminium nnector housing material Polyvinyl chloride (PVC) ximum data transfer rate 5000 Mbit/s ximum data transfer rate 5 Gbit/s bduct colour * Black	Cable length * Cable diameter Bend radius (min) Connector 1 dimensions (WxDxH) Connector 2 dimensions (WxDxH)	5 m 5.5 mm 4.8 cm 12 x 4.5 x 36 mm 6.6 x 7.3 x 34.4 mm
Connector material		Packaging data	
Contact material		Package type	Polybag
Connector contacts plating		Packaging content	
Cable Jacket material Conductor material		Quantity per pack *	1 pc(s)
Connector shielding		Operational conditions	
Connector shield material Connector housing material		Operating temperature (T-T) Storage temperature (T-T)	0 - 60 °C 0 - 60 °C
Maximum data transfer rate		Certificates	
Maximum data transfer rate		Certification	RoHS, REACH, UL
Cable type		Logistics data	
		Harmonized System (HS) code	84733080



4002888367448

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.