



Lindy HDMI to VGA Converter

Brand : Lindy

Product code: 38291

Product name : HDMI to VGA Converter

- Connects an HDMI equipped device to a VGA display
 - Supports resolutions up to 1920x1200 including 1080p
 - Direct signal conversion, without scaling
 - Quick and simple plug and play installation
 - 2 year warranty
- HDMI to VGA Converter

Lindy HDMI to VGA Converter:

The Lindy HDMI 1.3 to VGA converter converts signals from an HDMI equipped source into an analogue VGA signal. It supports resolutions up to 1080p and 1920x1200 for PC VGA displays. This allows the connection of modern HDMI capable devices, such as PC's, notebooks and ultrabooks, to an older VGA display or projector.

The converter can also be used to add another display to extend the available desktop workspace. It is also ideally suited for travelling due to its compact, lightweight form factor and convenient plug and play installation.



Features		Operational conditions	
Connector 1 form factor	Straight	Storage temperature (T-T)	-10 - 80 °C
Connector 2 form factor	Straight	Operating relative humidity (H-H)	5 - 95%
Cable length *	0.1 m	Certificates	
Connector 1 *	HDMI Type A (Standard)	Certification	CE, UKCA, FCC, RoHS, REACH
Connector 2 *	VGA (D-Sub)	Weight & dimensions	
Connector 1 gender *	Male	Cable diameter	4.8 mm
Connector 2 gender *	Female	Connector 1 dimensions (WxDxH)	37 x 42 x 14.5 mm
HDMI version	1.3	Connector 2 dimensions (WxDxH)	21 x 17.4 x 9.6 mm
Maximum resolution	1920 x 1080 pixels	Weight	27 g
Supported graphics resolutions	1920 x 1080 (HD 1080), 1920 x 1200 (WUXGA)	Packaging data	
Supported video modes	1080p	Package width	160 mm
Data transfer rate	4.95 Gbit/s	Package depth	20 mm
Maximum refresh rate	60 Hz	Package height	160 mm
Product colour	Black	Package weight	37 g
Chipset	Algotek AG6200A	Package type	Polybag
Jacket material	Polyvinyl chloride (PVC)	Packaging content	
Connector housing material	Acrylonitrile butadiene styrene (ABS)	Quantity per pack	1 pc(s)
Colour depth	12 bit	Logistics data	
Plug and Play	✓	Harmonized System (HS) code	84733080
Operational conditions			
Operating temperature (T-T)	0 - 70 °C		



4002888382915

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-FEB-2025. Prints or copies of Information are only valid on the printed Publication date