Lindy USB 3.0 Hub and Gigabit Ethernet Converter

Brand : Lindy

Product name : USB 3.0 Hub and Gigabit Ethernet Converter

Product code: 43176

USB 3.0 Hub and Gigabit Ethernet Converter

Lindy USB 3.0 Hub and Gigabit Ethernet Converter:

The Lindy USB 3.0 Hub and Gigabit Ethernet Converter allows users to conveniently connect a notebook or ultrabook to a Gigabit Ethernet network via a Type A USB port and also provides three additional USB 3.1 Gen 1 / 3.0 Type A ports.

This converter is ideal for notebooks which do not feature wired network connectivity and may only offer a limited number of USB ports.

With its small size and lightweight design this USB 3.0 Hub and Gigabit Ethernet Converter is easy and convenient to carry, and because it is powered by the USB Bus no power adapter is required.

Information about USB 3.0, 3.1 and 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps. USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

Ports & interfaces

Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A
Hub interfaces *	RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
Ports quantity *	4
Ethernet LAN (RJ-45) ports	1

Features

Data transfer rate *	5000 Mbit/s
Product colour	Black
Housing material	Plastic
Cable length	0.29 m
Certification	CE, UKCA, FCC, RoHS, REACH

Network

Ethernet interface type	Gigabit Ethernet
Ethernet LAN data rates	10,100,1000 Mbit/s
Networking standards	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u

Power

Power supply type	USB

System requirements

Windows operating systems supported	✔
Mac operating systems supported	✔
Linux operating systems supported	✔

Weight & dimensions

Weight & dimensions

Depth	110 mm
Height	20 mm
Weight	60 g

Packaging data

Quantity per pack	1 pc(s)
Package width	175 mm
Package depth	129 mm
Package height	30 mm
Package weight	100 g
Package type	Blister

Packaging content

Manual	✔

Operational conditions

Minimum operating temperature	0 °C
Maximum operating temperature	70 °C
Operating temperature (T-T)	0 - 70 °C
Operating temperature (T-T)	0 - 158 °F
Storage temperature (T-T)	-10 - 55 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	10 - 90%

Logistics data

Harmonized System (HS) code	84719000

Other features

Chipset	AX88179 (LAN), VL813 (Hub)

Weight & dimensions

Width	40 mm

4002888431767