

## Lindy 43176 keskitin USB 3.2 Gen 1 (3.1 Gen 1) Type-A 5000 Mbit/s musta

Tuotemerkki : Lindy Tuotekoodi: 43176

Tuotteen nimi: 43176

Lindy 43176. Isäntäkoneen käyttöliittymä: USB 3.2 Gen 1 (3.1 Gen 1) Type-A, Liittimiä: RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A. Tiedonsiirtonopeus: 5000 Mbit/s, Tuotteen väri: musta, Kotelon materiaali: Muovi. Ethernet-liitännän tyyppi: Gigabitti Ethernet, Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u. Virtalähteen tyyppi: USB. Tuotteen leveys: 40 mm, Tuotteen syvyys: 110 mm, Tuotteen korkeus: 20 mm





Ports & interfaces		Weight & dimensions	
Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A RI-45, USB 3.2 Gen 1 (3.1 Gen 1)	Depth Height	110 mm 20 mm
Hub interfaces *	Type-A	Weight	60 g
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3	Packaging data	
Ports quantity *	4	Quantity per pack	1 pc(s)
Ethernet LAN (RJ-45) ports	1	Package width	175 mm
Features		Package depth	129 mm
Data transfer rate *	5000 Mbit/s	Package height Package weight	30 mm 100 q
Product colour	Black	Package type	Blister
Housing material	Plastic	Packaging content	2.1316.
Cable length	0.29 m		
Certification	CE, UKCA, FCC, RoHS, REACH	Manual	✓
Network		Operational conditions	
Ethernet interface type	Gigabit Ethernet	<b>Operational conditions</b> Minimum operating temperature	0 °C
	10,100,1000 Mbit/s		0 °C 70 °C
Ethernet interface type	3	Minimum operating temperature	• •
Ethernet interface type Ethernet LAN data rates	10,100,1000 Mbit/s IEEE 802.3, IEEE 802.3ab, IEEE	Minimum operating temperature Maximum operating temperature Operating temperature (T-T)	70 °C 0 - 70 °C
Ethernet interface type Ethernet LAN data rates Networking standards	10,100,1000 Mbit/s IEEE 802.3, IEEE 802.3ab, IEEE	Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Operating temperature (T-T)	70 °C 0 - 70 °C 0 - 158 °F
Ethernet interface type Ethernet LAN data rates Networking standards  Power	10,100,1000 Mbit/s IEEE 802.3, IEEE 802.3ab, IEEE 802.3u	Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C 0 - 158 °F -10 - 55 °C
Ethernet interface type Ethernet LAN data rates Networking standards  Power Power supply type  System requirements Windows operating systems	10,100,1000 Mbit/s IEEE 802.3, IEEE 802.3ab, IEEE 802.3u	Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	70 °C 0 - 70 °C 0 - 158 °F -10 - 55 °C 10 - 90%
Ethernet interface type Ethernet LAN data rates Networking standards  Power Power supply type  System requirements Windows operating systems supported	10,100,1000 Mbit/s IEEE 802.3, IEEE 802.3ab, IEEE 802.3u  USB	Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C 0 - 158 °F -10 - 55 °C 10 - 90%
Ethernet interface type Ethernet LAN data rates Networking standards  Power Power supply type  System requirements Windows operating systems supported Mac operating systems supported	10,100,1000 Mbit/s IEEE 802.3, IEEE 802.3ab, IEEE 802.3u  USB	Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Logistics data	70 °C 0 - 70 °C 0 - 158 °F -10 - 55 °C 10 - 90% 10 - 90%
Ethernet interface type Ethernet LAN data rates Networking standards  Power Power supply type  System requirements Windows operating systems supported	10,100,1000 Mbit/s IEEE 802.3, IEEE 802.3ab, IEEE 802.3u  USB	Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Logistics data Harmonized System (HS) code	70 °C 0 - 70 °C 0 - 158 °F -10 - 55 °C 10 - 90% 10 - 90%

Weight & dimensions	
Width	40 mm



4002888431767

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.