



BenQ PD3205UA computer monitor 80 cm (31.5") 3840 x 2160 pixels 4K Ultra HD LCD Black

Brand : BenQ

Product code: 9H.LKGLA.TPE

Product name : PD3205UA

- Create with the comfort of ergo arm and enjoy the productivity
 - 32" 3840x2160 UHD 16:9 HDR IPS 4K Monitor
 - 99% sRGB and Rec.709 color spaces
 31.5", IPS (3840x2160), UHD, 4K, HDR10, 1000:1, 178°/178°, 5 ms, 60Hz, 16:9, 140 PPI, 1.07 billion colors, HDCP, 2.5Wx2, 100-240V, Puck G2, QSG, USB-C
 BenQ PD3205UA. Display diagonal: 80 cm (31.5"), Display resolution: 3840 x 2160 pixels, HD type: 4K Ultra HD, Display technology: LCD, Response time: 5 ms, Native aspect ratio: 16:9, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 2.0 / 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black



Display		Ports & interfaces	
Display diagonal *	80 cm (31.5")	DisplayPorts quantity	1
Display resolution *	3840 x 2160 pixels	DisplayPort version	1.4
HD type *	4K Ultra HD	Thunderbolt 3 ports quantity	1
Native aspect ratio *	16:9	Headphone out *	✓
Display technology *	LCD	Headphone outputs	1
Panel type *	IPS	Built-in KVM switch	✓
Backlight type	Direct LED	KVM switch ports quantity	1
Touchscreen *	✗	HDCP	✓
Display brightness (peak)	350 cd/m ²	HDCP version	2.2
Display brightness (typical)	250 cd/m ²		
Response time *	5 ms	Ergonomics	
Anti-glare screen	✓	VESA mounting *	✓
Screen shape *	Flat	Panel mounting interface	100 x 100 mm
Contrast ratio (typical) *	1000:1	Wall mountable	✓
Maximum refresh rate *	60 Hz	Height adjustment *	✓
Viewing angle, horizontal	178°	Adjustable height (max)	15 cm
Viewing angle, vertical	178°	Pivot	✓
Display number of colours *	1.07 billion colours	Pivot angle	0 - 90°
Pixel density	140 ppi	Swivelling	✓
High Dynamic Range (HDR) supported	✓	Swivel angle range	270 - 275°
High Dynamic Range (HDR) technology	High Dynamic Range 10 (HDR10)	Tilt adjustment	✓
Colour gamut standard	sRGB	Tilt angle range	-5 - 30°
Colour gamut	99%	Picture-in-Picture	✓
sRGB coverage (typical)	99%	On Screen Display (OSD)	✓
Performance			
Fast charging	✓		

Performance		Ergonomics	
ConnectShare (USB)	✓		Arabic, Simplified Chinese, Traditional Chinese, Czech, German, English, Spanish, French,
VESA Adaptive Sync support	✓		On Screen Display (OSD) languages
Flicker-free technology	✓		Hungarian, Italian, Japanese, Korean, Norwegian, Polish, Portuguese, Romanian, Russian, Swedish
Low Blue Light technology	✓		
Smart modes	Animation, M-Book, Personal		
Multimedia		Number of OSD languages	18
Multimedia		Power	
Number of speakers	2	Energy efficiency class (SDR) *	F
RMS rated power	5 W	Energy efficiency class (HDR) *	G
Built-in speaker(s) *	✓	Energy consumption (SDR) per 1000 hours *	30 kWh
Built-in camera *	✗	Energy consumption (HDR) per 1000 hours *	45 kWh
Design		Power consumption (typical) *	31.5 W
Market positioning *	Graphics design	Power consumption (standby) *	0.5 W
Product colour *	Black	Power consumption (max)	168 W
Frameless design	✓	AC input voltage	100 - 240 V
Front bezel colour	Black	Power supply type	Internal
Detachable stand	✓	Energy efficiency scale	A to G
Feet colour	Black	European Product Registry for Energy Labelling (EPREL) code	1335501
Ports & interfaces		Weight & dimensions	
Built-in USB hub *	✓	Width (with stand)	714.7 mm
USB hub version	2.0 / 3.2 Gen 1 (3.1 Gen 1)	Depth (with stand)	459.4 mm
USB upstream port type	USB Type-B	Height (with stand)	731.2 mm
Number of upstream ports	2	Weight (with stand)	10.1 kg
Number of USB Type-B upstream ports quantity	2	Width (without stand)	714.7 mm
USB Type-A downstream ports quantity	3	Depth (without stand)	82.4 mm
USB Type-C downstream ports quantity	1	Height (without stand)	422 mm
USB Type-C DisplayPort Alternate Mode	✓	Weight (without stand)	6.3 kg
USB Power Delivery (USB PD)	✓	Packaging data	
USB Power Delivery up to	65 W	Package type	Box
HDMI *	✓	Packaging content	
HDMI ports quantity	1	Stand included	✓
HDMI version	2.0	Quick start guide	✓
		Bundled software	Display Pilot
		Other features	
		Brand specific technologies	Eye Care+
		Screen mirroring	✓
		Hardware calibration	✓
		Certification	TUV, Solidworks, calman , Pantone , Pantone SkinTone



4718755090394

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 24-FEB-2025. Prints or copies of Information are only valid on the printed Publication date