

DELL Performance Dock - WD19DCS

Brand : DELL

Product code: M4XVJ

Product name : Dell Performance Dock - WD19DCS

DELL Performance Dock - WD19DCS. Connectivity technology: Wired, Host interface: USB 3.2 Gen 2 (3.1 Gen 2) Type-C. Ethernet LAN data rates: 10,100,1000 Mbit/s. Product colour: Black, Maximum digital resolution: 5120 x 2880 pixels. Power source type: DC, AC input voltage: 120 - 230 V, AC input frequency: 50 - 60 Hz. Windows operating systems supported: Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10...





| Ports & interfaces | | Power | |
|---|--|--|--|
| Connectivity technology * | Wired | Power supply | 210 W |
| Host interface * | USB 3.2 Gen 2 (3.1 Gen 2) Type-C | Power cable length | 0.8 m |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * | 3 | Software | |
| PowerShare | Image: A set of the set of the | Windows operating systems supported | Windows 10, Windows 10 Education, Windows 10 Education x64, Windows 10 Enterprise, Windows 10 Enterprise x64, Windows 10 Home, Windows 10 Home x64, Windows 10 IOT Core, Windows 10 IOT Enterprise, Windows 10 Pro, Windows 10 Pro x64, Windows 10 x64 |
| HDMI ports quantity * | 1 | | |
| HDMI version | 2.0 | | |
| DisplayPorts quantity | 2 | | |
| DisplayPort version | 1.4 | | |
| Microphone in * | × | | |
| DC-in jack | Image: A start of the start of | Linux operating systems supported | ✓ |
| Network | | Operational conditions | |
| Ethernet LAN * | Image: A set of the set of the | Operating temperature (T-T) | 0 - 35 °C |
| Ethernet LAN (RJ-45) ports | 1 | Storage temperature (T-T) | -20 - 60 °C |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | Operating relative humidity (H-H) | 10 - 80% |
| Performance | | Storage relative humidity (H-H) | 5 - 90% |
| Card reader integrated * | × | Weight & dimensions | |
| Maximum digital resolution | 5120 x 2880 pixels | Width | 205 mm |
| VESA mounting | Image: A second s | Depth | 90 mm |
| Product colour * | Black | Height | 29 mm |
| On/off switch | Image: A set of the set of the | Weight | 585 g |
| LED indicators | 1 | Packaging data | |
| Power | | Quantity per pack | 1 pc(s) |
| Power source type | DC | Package width | 300 mm |
| AC input voltage | 120 - 230 V | Package depth | 315 mm |
| AC input frequency | 50 - 60 Hz | Package height | 62 mm |

Logistics data

Harmonized System (HS) code

84733020

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.