

## BenQ ST5502S Digitaalinen litteä infotaulu 139,7 cm (55") LCD 400 cd/m² 4K Ultra HD musta Sisäänrakennettu prosessori Android 8.0

Tuotemerkki: BenQ Tuotekoodi: 9H.F7HPT.RA4

Tuotteen nimi: ST5502S







Display		Performance	
Panel type	IPS	Purpose *	Corporate
Display diagonal *	139.7 cm (55")	Power	
Display technology * LCD  Display resolution * 3840 x 2160 pixels  Display brightness * 400 cd/m²  HD type * 4K Ultra HD  Touchscreen * X  Native aspect ratio 16:9	3840 x 2160 pixels 400 cd/m <sup>2</sup> 4K Ultra HD	Power consumption (typical) * Power consumption (standby) * Energy efficiency class (SDR) Energy consumption (SDR) per 1000 hours AC input voltage	134 W 0.5 W G 134 kWh
Contrast ratio (typical)	1200:1	AC input frequency	50 - 60 Hz
Active display area (W x H)	1206.6 x 680.4 mm	Energy efficiency scale	A to G
Panel life	30000 h	Computer system	
RGB colour space	NTSC	Computer system *	✓
Ports & interfaces		Built-in processor *	/
HDMI ports quantity * HDMI version HDMI input ports quantity DVI port * VGA (D-Sub) input ports	2 2.0 2 •• 1	Processor architecture Processor cores Internal memory Internal storage capacity Operating system installed	ARM Cortex-A53+Cortex-A73 4 3 GB 16 GB Android 8.0
USB port *	✓	Weight & dimensions	
USB ports quantity USB version Ethernet LAN * Ethernet LAN data rates Wi-Fi *	2 2.0  10,100 Mbit/s	Display width Display depth Display height Display weight	1241.8 mm 63.5 mm 712.6 mm 16.6 kg
		Packaging data	
PC Audio in RS-232 interface	<b>✓</b>	Package width	1350 mm
Card reader integrated	✓	Package depth Package height	185 mm 910 mm

Ports & interfaces		Packaging data		
Compatible memory cards	MicroSD (TransFlash)	Package weight	22 kg	
PC Audio out	✓	Packaging content		
Audio		Remote control included	✓	
Built-in speaker(s) *	✓	Cables included	HDMI	
Number of built-in speakers	2	Operational conditions		
RMS rated power	20 W	Operating temperature (T-T)	0 - 40 °C	
Design		Operating relative humidity (H-H)	10 - 80%	
Product design *	Digital signage flat panel	Storage temperature (T-T)	-20 - 60 °C	
Placement supported *	Indoor	Storage relative humidity (H-H)	10 - 80%	
Orientation	Horizontal/Vertical			
Product colour *	Black			
VESA mounting *	✓			
Panel mounting interface	400 x 400 mm			

