## Lenovo ThinkSystem SR250 V2 server 0 GB Rack (1U) Intel Xeon E E-2378 2.6 GHz 32 GB DDR4-SDRAM 450 W

Brand: Lenovo Product family: ThinkSystem Product code: 7D7QA031EA

**Product name :** SR250 V2

- No OS
- Intel Xeon E-2378 (16MB Cache, 2.6GHz)
- 32GB DDR4-SDRAM (1 x 32)
- XCC Enterprise

Intel Xeon E-2378 (16MB Cache, 2.6GHz), 32GB DDR4-SDRAM, Intel UHD Graphics P630, LAN, 5350-8I, XCC Enterprise, 450W, No OS

Lenovo ThinkSystem SR250 V2 server 0 GB Rack (1U) Intel Xeon E E-2378 2.6 GHz 32 GB DDR4-SDRAM 450 W:

The Lenovo ThinkSystem SR250 V2 is a high-value single-socket 1U rack server for growing businesses that need optimized performance and flexibility for future growth, along with enterprise-class reliability, management, and security. The server supports the new Intel Xeon E-2300 Series processors, formerly codenamed "Rocket Lake".

This product guide provides essential presales information to understand the ThinkSystem SR250 V2 server, its key features and specifications, components and options, and configuration guidelines. This guide is intended for technical specialists, sales specialists, sales engineers, IT architects, and other IT professionals who want to learn more about the SR250 V2 and consider its use in IT solutions

Processor		Design	
Processor manufacturer *	Intel	Rack rails	✓
Processor family * Intel Xeon E Processor model * E-2378 Processor frequency * 2.6 GHz Processor boost frequency 4.8 GHz Processor cores 8 Processor cache 16 MB Motherboard chipset Intel C256 Number of processors installed 1 Execute Disable Bit ✓ Idle States ✓ Embedded options available	E-2378 2.6 GHz 4.8 GHz 8 16 MB	Performance	
		Remote administration Trusted Platform Module (TPM) Trusted Platform Module (TPM) version	XCC Enterprise  ✓ 2.0
		Software	
	1 ✓	Operating system installed *  Compatible operating systems *	X Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi
·	^	Processor special features	
Memory	22.60	CPU configuration (max)	1
Internal memory * Internal memory type *	32 GB DDR4-SDRAM	Enhanced Intel SpeedStep Technology	✓
Memory slots ECC	4x DIMM	Intel Virtualization Technology for Directed I/O (VT-d)	✓
Memory layout (slots x size)	1 x 32 GB	Intel Trusted Execution Technology	<b>✓</b>
Maximum internal memory *	128 GB	Intel VT-x with Extended Page Tables (EPT)	✓
Storage		Intel TSX-NI	<b>✓</b>
Total storage capacity *	0 GB	Intel Clear Video Technology	<b>✓</b>
RAID support * Supported RAID controllers	<b>✓</b> 5350-8I	Intel Software Guard Extensions (Intel SGX)	✓
Hot-swap	✓	Intel 64	<b>✓</b>
Optical drive type * Internal drive bays	<b>x</b> 8	Intel Virtualization Technology (VT-x)	<b>✓</b>
Graphics		Power	
On-board graphics card	<b>✓</b>	Power supply *	450 W
On-board graphics card model	Intel UHD Graphics P630	Operational conditions	
		Operating temperature (T-T) Storage temperature (T-T)	5 - 45 °C -40 - 60 °C

Network		Operational conditions	
Ethernet LAN	✓	Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude	8 - 90% 8 - 90% 0 - 3050 m
Ports & interfaces			
USB 2.0 ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A	1	Weight & dimensions	
ports quantity	1	Width	435 mm
USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity	2	Depth Height	545 mm 43 mm
VGA (D-Sub) ports quantity	1	Weight	12.3 kg
Serial ports quantity	1		
Design			
Chassis type *	Rack (1U)		
Product colour	Black, Metallic		
Rack mounting	✓		

