

KYOCERA ECOSYS PA3500cx Väri 1200 x 1200 DPI A4

Tuotemerkki : KYOCERA

Tuotekoodi: 1102YJ3NL0

Tuotteen nimi : ECOSYS PA3500cx

KYOCERA ECOSYS PA3500cx. Tulostustekniikka: Laser, Väri. Värikasettien määrä: 4, Suurin toimintajakso: 100000 sivua kuukaudessa. Suurin resoluutio: 1200 x 1200 DPI. Suurin ISO A-luokan paperikoko: A4. Tulostusnopeus (musta, normaalilaatu, A4/US Letter): 35 ppm, Kaksipuolinen tulostus. Tuotteen väri: musta, Valkoinen



Printing		Performance	
Duplex printing mode	Auto	Internal memory *	1024 MB
Print speed (colour, normal quality, A4/US Letter)	35 ppm	Built-in processor	✓
Colour *	✓	Sound pressure level (printing)	51 dB
Print technology *	Laser	Sound power level (standby)	30 dB
Duplex printing *	✓	Design	
Maximum resolution *	1200 x 1200 DPI	Market positioning *	Business
Print speed (black, normal quality, A4/US Letter) *	35 ppm	Product colour *	Black, White
Duplex print speed (black, normal quality, A4/US Letter)	17.5 ppm	Built-in display *	✓
Duplex print speed (colour, normal quality, A4/US Letter)	17.5 ppm	Colour display	✗
Warm-up time	23 s	Control type	Buttons
Time to first page (black, normal)	5.7 s	Power	
Time to first page (colour, normal)	5.7 s	Power consumption (printing) *	496.4 W
Economical printing	✓	Power consumption (ready)	11.8 W
Features		Power consumption (PowerSave)	0.4 W
Maximum duty cycle *	100000 pages per month	Power consumption (off)	0.1 W
Recommended duty cycle	1000 - 3500 pages per month	Energy Star Typical Electricity Consumption (TEC)	0.32 kWh/week
Printing colours *	Black, Cyan, Magenta, Yellow	AC input voltage	220 - 240 V
Number of print cartridges *	4	AC input frequency	50/60 Hz
Page description languages *	JPEG, OpenXPS, PCL 5c, PCL 6, PCL XL, PCLm, PDF, PWG, PostScript 3, TIFF, URF, XPS	System requirements	
Replacement cartridges	TK-5370	Windows operating systems supported	✓
Input & output capacity			
Total number of input trays *	2		
Total input capacity *	650 sheets		

Input & output capacity		System requirements	
Total output capacity *	250 sheets		Mac OS X 10.0 Cheetah, Mac OS X 10.1 Puma, Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura
Multi-Purpose tray	✓	Mac operating systems supported	
Multi-Purpose tray input capacity	100 sheets		
Maximum number of input trays	5		
Maximum input capacity	2300 sheets		
Maximum output capacity	250 sheets		
Paper handling			
Maximum ISO A-series paper size *	A4		
Paper tray media types *	Banner, Plain paper, Pre-printed		
ISO A-series sizes (A0...A9) *	A4, A5, A6		
ISO B-series sizes (B0...B9)	B5, B6		
Non-ISO print media sizes	Folio, Legal, Letter		
Paper tray media weight	60 - 220 g/m ²	Linux operating systems supported	✓
Ports & interfaces		Other operating systems supported	ChromeOS
Direct printing *	✓	Operational conditions	
USB port *	✓	Operating temperature (T-T)	10 - 32.5 °C
USB 2.0 ports quantity	1	Storage temperature (T-T)	-20 - 40 °C
Optional connectivity	Ethernet, Wireless LAN	Operating relative humidity (H-H)	10 - 80%
Network		Storage relative humidity (H-H)	10 - 90%
Wi-Fi *	✗	Operating altitude	0 - 3500 m
Ethernet LAN *	✓	Sustainability	
Cabling technology	10/100/1000Base-T(X)	Sustainability compliance	✓
Ethernet LAN data rates	10,100,1000 Mbit/s	Weight & dimensions	
Security algorithms	SNMPv3, TLS	Width	394 mm
Mobile printing technologies	Apple AirPrint, Kyocera Mobile Print, Mopria Print Service	Depth	533 mm
		Height	392.5 mm
		Weight	33 kg
		Packaging data	
		Package width	702 mm
		Package depth	567 mm
		Package height	561 mm
		Package weight	40 kg
		Packaging content	
		Cartridge(s) included	✓
		Included cartridge capacity (black)	3500 pages
		Included cartridge capacity (CMY)	2500 pages
		Cables included	AC
		Technical details	
		Compliance certificates	CE, GS mark, cTUVus



0632983071625



632983071625

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.