NETGEAR

NETGEAR M4500-32C Hallittu L2/L3/L4 1U musta

Tuotemerkki : NETGEAR

Tuotekoodi: CSM4532-100EUS

Tuotteen nimi : M4500-32C

NETGEAR M4500-32C. Kytkin tyyppi: Hallittu, Kytkinkerros: L2/L3/L4. USB 2.0 -porttien määrä: 1, Console-portti: RJ-45. MAC-osoitetaulukko: 32000 entries, Kytkentäkapasiteetti: 6400 Gbit/s. Verkkostandardit: IEEE 802.1AX, IEEE 802.3ad. Virtaliitin: DC-tulo jakkiliitin. Telineasennus, Kotelo: 1U






Management features		Security	
Switch type *	Managed	BPDU filtering/protection	1
Switch layer	L2/L3/L4	Multicast features	
Quality of Service (QoS) support		Multicast support	1
Web-based management		Protocols	
ARP inspection			Web GUI, HTTPs, CLI, Telnet, SSH,
System event log Ports & interfaces	,	Management protocols	SNMP, MIBs RSPAN, Radius Users, TACACS+
Fiber optic connector	QSFP+	Design	
Console port	RJ-45	Rack mounting *	1
QSFP28 ports quantity	32	Form factor	10
USB 2.0 ports quantity	1	Product colour	Black
Power connector	DC-in jack	Housing material	Metal
Network		Reset button	1
Networking standards *	IEEE 802.1AX, IEEE 802.3ad	LED indicators	1
10G support * Port mirroring	v v	Electromagnetic compatibility	CE, FCC 15 A, VCCI A, A EN 55022, (CISPR 22) A, EN 50082-1, EN 55024
Flow control support	1	Performance	
Link aggregation	1	Built-in processor	1
Rate limiting	1	Memory type	DDR3-SDRAM
Auto MDI/MDI-X	1	Internal memory	8000 MB
Spanning tree protocol	1	Flash memory	256 MB
Auto-sensing	1	Noise level	64 dB
Auto-negotiation	1	Power	
VLAN support	1	Power consumption (max)	426 W
Virtual LAN features	Private VLAN, Tagged VLAN, Voice	Power over Ethernet (PoE)	
Number of VLANs	VLAN 4000	Power over Ethernet (PoE) *	×
Optical fiber	4000	Weight & dimensions	
•	100BASE-X	Weight	9.78 kg
Fiber ethernet cabling technology	TUUDAJE-V	Packaging content	
Data transmission		User guide	1
Switching capacity *	6400 Gbit/s	Manual	1
MAC address table *	32000 entries		

Security		Packaging data	
DHCP features	DHCP client, DHCP relay, DHCP server	Package type Package width	Box 593 mm
Access Control List (ACL)	✓	Package depth	888 mm
IGMP snooping	1	Package height	186 mm
Security algorithms	HTTPS, SNMP, SSH	Package weight	20.5 kg
SSH/SSL support	1	Logistics data	
		Harmonized System (HS) code	85176990

Harmonized System (HS) code

Products per master (outer) case 1 pc(s)





606449145731

0606449145731

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.