NETGEAR GSM4210PD-100EUS verkkokytkin Hallittu L2/L3 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta

Tuotemerkki : NETGEAR Tuotekoodi: GSM4210PD-100EUS

Tuotteen nimi: GSM4210PD-100EUS







Management features		Performance	
Switch type * Switch layer Quality of Service (QoS) support	Managed L2/L3 ✓	Built-in processor Processor model Processor frequency Internal memory	ARM Cortex-A9 1250 MHz 2048 MB
Ports & interfaces		Noise level	30.06 dB
Basic switching RJ-45 Ethernet ports quantity *	ŭ	Power	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power source *	AC/DC
Network		Power supply included * AC input voltage	220 - 240 V
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ad, IEEE	AC input frequency	50 - 60 Hz
		Power over Ethernet (PoE)	
	802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3x	Power over Ethernet (PoE) *	1
Full duplex	✓	Power over Ethernet plus (PoE+) ports quantity	8
Link aggregation	✓	Power over Ethernet (PoE) power	30 W
Broadcast storm control	✓	per port Total Power over Ethernet (PoE)	
Rate limiting	✓	budget	110 W
Spanning tree protocol	✓	Operational conditions	
Data transmission		Operating temperature (T-T)	0 - 50 °C
Switching capacity * MAC address table *	24 Gbit/s 16000 entries	Storage temperature (T-T) Operating relative humidity (H-H)	-20 - 70 °C 0 - 90%
Store-and-forward	1	Storage relative humidity (H-H)	0 - 95%
Security	DHCP Option 82, DHCP relay, DHCP	Operating altitude Non-operating altitude	0 - 3000 m 0 - 3000 m
DHCP features	server, DHCP snooping, DHCPv6 client, DHCPv6 relay, DHCPv6	Heat dissipation	559.555 BTU/h
	server, DHCPv6 snooping	Weight & dimensions	
Access Control List (ACL)	✓	Width	210 mm
IGMP snooping	✓	Depth	140 mm
SSH/SSL support	✓	Height Weight	40 mm 967 g
Loop protection	✓	Packaging content	· 3
BPDU filtering/protection	✓		,
Authentication	MAC-based authentication	User guide	√
Authentication type	RADIUS	Manual	✓
Multicast features			
Multicast support	✓		
IPv4 multicast entries	2000		

Design

Rack mounting *

✓

Product colour

Black

LED indicators

PoE, Power, Status





606449160192

0606449160192

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.