## NETGEAR GS516UP Hallitsematon Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki Harmaa

Tuotemerkki : NETGEAR

Tuotekoodi: GS516UP-100EUS

## Tuotteen nimi : GS516UP

NETGEAR GS516UP. Kytkin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 16. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 32 Gbit/s. Verkkostandardit: IEEE 802.3, IEEE 802.3af, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3i, IEEE 802.3p, IEEE.... Power over Ethernet -tuki. Telineasennus

Management features		Performance	
Switch type *	Unmanaged	Mean time between failures (MTBF)	1213791 h
Quality of Service (QoS) support	<ul> <li>Image: A start of the start of</li></ul>	Power	
Ports & interfaces		Power supply included *	1
Basic switching RJ-45 Ethernet ports quantity *		AC input voltage AC input frequency	100 - 240 V 50 - 60 Hz
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Input current Power consumption (max)	8 - 4 A 456.8 W
Network		Power over Ethernet (PoE)	
Not offer all the states and the state of the	IEEE 802.3, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE	Power over Ethernet (PoE) *	1
Networking standards *	802.3bt, IEEE 802.3i, IEEE 802.3p, IEEE 802.3u	Power over Ethernet plus (PoE+) ports quantity	16
10G support * Full duplex	×	Power over Ethernet (PoE) power per port	60 W
Half duplex	<i>x</i>	Total Power over Ethernet (PoE) budget	380 W
Auto MDI/MDI-X	<ul> <li>Image: A start of the start of</li></ul>	Operational conditions	
Data transmission		Operating temperature (T-T)	0 - 50 °C
Switching capacity * MAC address table * Latency (1 Gbps) Jumbo frames support	32 Gbit/s 8000 entries 12 μs ✓	Storage temperature (T-T) Operating relative humidity (H-H) Operating altitude Heat dissipation	-20 - 70 °C 10 - 90% 0 - 3000 m 1559.5152 BTU/h
Packet forwarding rate (1 Gbps)	1448000 pps	Weight & dimensions	
Packet buffer memory	0.192 MB	Width	390 mm
Design		Depth	220 mm
Rack mounting *	✓	Height	43 mm
Product colour	Grey	Weight	2.6 kg
Housing material	Metal	Logistics data	
LED indicators Number of fans	Activity, Link, PoE, Power, Speed 3 fan(s)	Harmonized System (HS) code	85176990





606449149746

0606449149746



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.