

NETGEAR GSM4212P-111EUS verkkokytkin Hallittu L2/L3 Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki 1U musta

Tuotemerkki : NETGEAR

Tuotekoodi: GSM4212P-111EUS

Tuotteen nimi : GSM4212P-111EUS

NETGEAR GSM4212P-111EUS. Kytkin tyyppi: Hallittu, Kytinkerros: L2/L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 10. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 24 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ad, IEEE.... Power over Ethernet -tuki. Telineasennus, Kotelo: 1U



Management features		Multicast features	
Switch type *	Managed	IPv6 multicast entries	2000
Switch layer	L2/L3	Design	
Quality of Service (QoS) support	✓	Rack mounting *	✓
Ports & interfaces		Form factor	1U
Basic switching RJ-45 Ethernet ports quantity *	10	Product colour	Black
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	LED indicators	PoE, Power, Status
SFP module slots quantity	2	Performance	
Network		Built-in processor	✓
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3x	Processor model	ARM Cortex-A9
		Processor frequency	1250 MHz
10G support *	✗	Internal memory	2048 MB
Full duplex	✓	Noise level	30.06 dB
Link aggregation	✓	Mean time between failures (MTBF)	778769 h
Broadcast storm control	✓	Power over Ethernet (PoE)	
Rate limiting	✓	Power over Ethernet (PoE) *	✓
Spanning tree protocol	✓	Power over Ethernet plus (PoE+) ports quantity	8
VLAN support	✓	Power over Ethernet (PoE) power per port	30 W
Virtual LAN features	MAC address-based VLAN, Private VLAN, Protocol-based VLAN, Tagged VLAN, Voice VLAN	Total Power over Ethernet (PoE) budget	150 W
Number of VLANs	4093	Operational conditions	
Data transmission		Operating temperature (T-T)	0 - 50 °C
Switching capacity *	24 Gbit/s	Storage temperature (T-T)	-20 - 70 °C
Throughput	17.86 Mpps	Operating relative humidity (H-H)	0 - 90%
MAC address table *	16000 entries	Storage relative humidity (H-H)	0 - 95%
Store-and-forward	✓	Operating altitude	0 - 3000 m
Latency (1 Gbps)	2.27 µs	Non-operating altitude	0 - 3000 m
		Heat dissipation	559.555 BTU/h
		Weight & dimensions	
		Width	440 mm
		Depth	200 mm
		Height	43.2 mm

Security		Weight & dimensions	
DHCP features	DHCP Option 82, DHCP relay, DHCP server, DHCP snooping, DHCPv6 client, DHCPv6 relay, DHCPv6 server, DHCPv6 snooping	Weight	2.85 kg
Access Control List (ACL)	✓	Packaging content	
IGMP snooping	✓	User guide	✓
SSH/SSL support	✓	Manual	✓
Loop protection	✓		
BPDU filtering/protection	✓		
Authentication	MAC-based authentication		
Authentication type	RADIUS		
Multicast features			
Multicast support	✓		
IPv4 multicast entries	2000		



0606449159691



606449159691

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.