

# NETGEAR GS748T Hallittu L2+ Gigabit Ethernet (10/100/1000) Sininen



**Tuotemerkki :** NETGEAR

**Tuotekoodi:** GS748T-500EUS

**Tuotteen nimi :** GS748T

NETGEAR GS748T. Kytkin tyyppi: Hallittu, Kytinkerros: L2+. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 48. Täysin kaksipuolinen. MAC-osoitetaulukko: 8000 entries. Verkkostandardit: IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. Virtaliitin: DC-tulo jakkiliitin. Telineasennus

Management features		Performance	
Switch type *	Managed	Compatible operating systems	Windows, MAC, Linux
Switch layer	L2+	Noise level	52 dB
Quality of Service (QoS) support	✓	Mean time between failures (MTBF)	108000 h
Web-based management	✓	<b>Power</b>	
<b>Ports &amp; interfaces</b>		Power source *	AC
Basic switching RJ-45 Ethernet ports quantity *	48	AC input voltage	100 - 240 V
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	AC input frequency	50 - 60 Hz
Combo SFP ports quantity	2	Power consumption (typical)	66 W
SFP module slots quantity	2	Power consumption (max)	70 W
Power connector	DC-in jack	<b>Power over Ethernet (PoE)</b>	
<b>Network</b>		Power over Ethernet (PoE) *	✗
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	<b>Operational conditions</b>	
10G support *	✗	Operating temperature (T-T)	0 - 40 °C
Full duplex	✓	Storage temperature (T-T)	-10 - 70 °C
Flow control support	✓	Operating relative humidity (H-H)	0 - 90%
Link aggregation	✓	Storage relative humidity (H-H)	0 - 95%
Rate limiting	✓	Operating altitude	0 - 3000 m
Spanning tree protocol	✓	Non-operating altitude	0 - 3000 m
VLAN support	✓	<b>Weight &amp; dimensions</b>	
Number of VLANs	64	Width	305 mm
<b>Data transmission</b>		Depth	43 mm
MAC address table *	8000 entries	Height	440 mm
Latency (10-100 Mbps)	20 µs	Weight	4.9 kg
Jumbo frames support	✓	<b>Packaging content</b>	
Packet buffer memory	1.632 MB	Cables included	LAN (RJ-45)
<b>Security</b>		Quick start guide	✓
DHCP features	DHCP client	User guide	✓
Access Control List (ACL)	✓	Manual	✓
<b>Design</b>		<b>Certificates</b>	
Rack mounting *	✓	Certification	CE mark, commercial FCC Part 15 Class A VCCI Class A EN 55022 (CISPR 22), Class A EN 50082-1 EN 55024 C-Tick
Product colour	Blue	<b>Logistics data</b>	
Safety	UL listed (UL 1950)/cUL, IEC 950/EN 60950	Harmonized System (HS) code	85176990



0606449098242



606449098242



4056572857340

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.