

NETGEAR GS308-300PES verkkokytkin Hallitsematon L2 Gigabit Ethernet (10/100/1000) musta

Tuotemerkki : NETGEAR

Tuotekoodi: GS308-300PES

Tuotteen nimi : GS308-300PES



NETGEAR GS308-300PES. Kytkin tyyppi: Hallitsematon, Kytinkerros: L2. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 8. MAC-osoitetaulukko: 8000 entries, Kytkentäkapasiteetti: 16 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u. Virtaliitin: DC-tulo jakkiliitin. Seinäkiinnitteinen

Management features		Design	
Switch type *	Unmanaged	Rack mounting *	✗
Switch layer	L2	Product colour	Black
Quality of Service (QoS) support	✓	Housing material	Metal
Ports & interfaces		LED indicators	Activity, Link, Power
Basic switching RJ-45 Ethernet ports quantity *	8	Wall mountable	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Performance	
Gigabit Ethernet (copper) ports quantity	8	Mean time between failures (MTBF)	3711898 h
Power connector	DC-in jack	Power	
Network		Power consumption (max)	3.04 W
Networking standards *	IEEE 802.1p, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u	Power over Ethernet (PoE)	
10G support *	✗	Power over Ethernet (PoE) *	✗
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T	Operational conditions	
Flow control support	✓	Operating temperature (T-T)	0 - 40 °C
Auto MDI/MDI-X	✓	Storage temperature (T-T)	-20 - 70 °C
Auto-sensing	✓	Operating relative humidity (H-H)	0 - 90%
Cable length detection	✓	Storage relative humidity (H-H)	0 - 95%
Data transmission		Operating altitude	0 - 3000 m
Switching capacity *	16 Gbit/s	Heat dissipation	10.4 BTU/h
Forwarding rate	1.448 Mpps	Weight & dimensions	
MAC address table *	8000 entries	Width	158 mm
Latency (1 Gbps)	2.6 µs	Depth	101 mm
Jumbo frames support	✓	Height	29 mm
Jumbo frames	9216	Weight	390 g
Packet buffer memory	128 MB	Certificates	
		Certification	CE Mark FCC Part 15 Class B IC Class B RCM CCC VCCI KC
		Logistics data	
		Harmonized System (HS) code	85176990



0606449140149



606449140149

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.