

NETGEAR GS308PP Hallitsematon Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta

Tuotemerkki : NETGEAR

Tuotekoodi: GS308PP-100EUS

Tuotteen nimi : GS308PP



NETGEAR GS308PP. Kytin tyyppi: Hallitsematon. Peruskäytävä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic käytävä RJ-45 Ethernet-porttien määrä: 8. Täysin kaksipuolinen. MAC-osoitetaulukko: 4000 entries, Käytäväkapasiteetti: 16 Gbit/s. Verkko-standardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. DC-syöttöjännite: 54 V. Virtaliitin: DC-tulo jakkiliitin. Power over Ethernet -tuki. Seinäkiinnitteinen, Telineasennus

Management features		Performance	
Switch type *	Unmanaged	Mean time between failures (MTBF)	2752476 h
Quality of Service (QoS) support	✓	Power	
Ports & interfaces		DC input voltage	54 V
Basic switching RJ-45 Ethernet ports quantity *	8	Input current	1.66 A
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power consumption (max)	87.9 W
Power connector	DC-in jack	Power over Ethernet (PoE)	
Network		Power over Ethernet (PoE) *	✓
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE) type supported	PoE+
10G support *	✗	Power over Ethernet plus (PoE+) ports quantity	8
Full duplex	✓	Power over Ethernet (PoE) power per port	30 W
Flow control support	✓	Total Power over Ethernet (PoE) budget	130 W
Auto MDI/MDI-X	✓	Operational conditions	
Auto-sensing	✓	Operating temperature (T-T)	0 - 40 °C
Auto-negotiation	✓	Storage temperature (T-T)	-20 - 70 °C
Data transmission		Operating relative humidity (H-H)	0 - 90%
Switching capacity *	16 Gbit/s	Operating altitude	0 - 3000 m
MAC address table *	4000 entries	Heat dissipation	300.6 BTU/h
Latency (1 Gbps)	3 µs	Weight & dimensions	
Jumbo frames support	✓	Width	236 mm
Jumbo frames	9216	Depth	102 mm
Packet forwarding rate (1 Gbps)	1448000 pps	Height	27 mm
Packet buffer memory	0.192 MB	Weight	600 g
Design		Certificates	
Rack mounting *	✓	Certification	CE Mark, FCC Part 15 Class A, IC Class A, RCM, VCCI, BSMI, KC
Product colour	Black	Logistics data	
Housing material	Metal	Harmonized System (HS) code	85176990
LED indicators	Activity, Link, PoE, Power, Speed		
Wall mountable	✓		



0606449146851



606449146851

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.