

NETGEAR GS316PP Hallitsematon Gigabit Ethernet (10/100/1000) Power over Ethernet -tuki musta



Tuotemerkki : NETGEAR

Tuotekoodi: GS316PP-100EUS

Tuotteen nimi : GS316PP

NETGEAR GS316PP. Kytin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: Gigabit Ethernet (10/100/1000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 16. Täysin kaksipuolinen. MAC-osoitetaulukko: 4000 entries, Kytkentäkapasiteetti: 32 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE.... DC-syöttöjännite: 54 V. Virtaliitin: DC-tulo jakkiliitin. Power over Ethernet -tuki. Seinäkiinnitteinen



Management features		Design	
Switch type *	Unmanaged	Wall mountable	✓
Quality of Service (QoS) support	✓	Performance	
Ports & interfaces		Mean time between failures (MTBF)	2362192 h
Basic switching RJ-45 Ethernet ports quantity *	16	Power	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	DC input voltage	54 V
Power connector	DC-in jack	Input current	3.7 A
Network		Power consumption (max)	195.9 W
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x	Power over Ethernet (PoE)	
10G support *	✗	Power over Ethernet (PoE) *	✓
Full duplex	✓	Power over Ethernet plus (PoE+) ports quantity	16
Flow control support	✓	Power over Ethernet (PoE) power per port	30 W
Auto MDI/MDI-X	✓	Total Power over Ethernet (PoE) budget	183 W
Auto-sensing	✓	Operational conditions	
Auto-negotiation	✓	Operating temperature (T-T)	0 - 40 °C
Data transmission		Storage temperature (T-T)	-20 - 70 °C
Switching capacity *	32 Gbit/s	Operating relative humidity (H-H)	0 - 90%
MAC address table *	4000 entries	Operating altitude	0 - 3000 m
Latency (1 Gbps)	3.7 µs	Heat dissipation	669.9 BTU/h
Jumbo frames support	✓	Weight & dimensions	
Jumbo frames	9216	Width	286 mm
Packet forwarding rate (1 Gbps)	1448000 pps	Depth	102 mm
Packet buffer memory	1 MB	Height	27 mm
Security		Weight	880 g
Queue scheduling algorithms	Weighted Round Robin (WRR)	Certificates	
Design		Certification	CE, FCC Part A, IC A, RCM, VCCI, BSMI, KC, CB, CE LVD
Rack mounting *	✗	Logistics data	
Product colour	Black	Harmonized System (HS) code	85176990
Housing material	Metal		
LED indicators	Activity, Link, PoE, Power, Speed		



0606449146912



606449146912

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.