NETGEAR M4350-8X8F Hallittu L3 10G Ethernet (100/1000/10000) 1U musta

Tuotemerkki : NETGEAR Tuotekoodi: XSM4316-100NES

tekoodi: XSM4316-100NES

Tuotteen nimi: M4350-8X8F

NETGEAR M4350-8X8F. Kytkin tyyppi: Hallittu, Kytkinkerros: L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: 10G Ethernet (100/1000/10000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 8. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 320 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Qav, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE.... Virtaliitin: AC-in-liitin. Telineasennus, Kotelo: 1U



Management features		Security	
Switch type * Switch layer Quality of Service (QoS) support	Managed L3 ✓	Authentication type Queue scheduling algorithms	RADIUS, TACACS+ Strict Priority Queue (SPQ), Weighted random early detection (WRED)
Web-based management	✓	Multicast features	
ARP inspection	✓	Multicast support	✓
Ports & interfaces Basic switching RJ-45 Ethernet ports	8	Multicast Listener Discovery (MLD) snooping	✓
quantity * Basic switching RJ-45 Ethernet ports		Protocols	
type * 10G Ethernet (copper) ports quantity	10G Ethernet (100/1000/10000) 8	Management protocols GARP VLAN Registration Protocol (GVRP)	SNMP V1, V2, V3 ✓
SFP+ module slots quantity Power connector	8 AC-in jack	Routing protocols	OSPF, OSPFv2, OSPFv3, RIP, RIP-1, RIP-2
Network		Design	
Networking standards * 10G support *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Qav, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ak, IEEE 802.3bz, IEEE 802.3u	Rack mounting * Stackable * Form factor Product colour LED indicators	1U Black
Full duplex	√	Airflow direction	Front-to-back airflow
Policy-based routing	✓	Performance	Trone to back aimon
Flow control support Link aggregation Broadcast storm control Rate limiting Spanning tree protocol 6to4 tunnel IPv4 routes IPv6 routes	 ✓ ✓ ✓ ✓ 512 256 	Built-in processor Processor model Processor frequency Memory type Internal memory Flash memory sFlow Power	ARM Cortex-A57 1800 MHz DDR4-SDRAM 2048 MB 512 MB
VLAN support	✓	Power source *	AC

Power supply included *

Network		Power	
Virtual LAN features	MAC address-based VLAN, Private VLAN, Voice VLAN 4093	Power consumption (typical)	81.1 W
Number of VLANs		Power over Ethernet (PoE)	
Data transmission		Power over Ethernet (PoE) *	×
Switching capacity *	320 Gbit/s	Other features	
Throughput	238.08 Mpps	Power supply	240 W
MAC address table *	16000 entries	Operational conditions	
Store-and-forward	2 29 115	Operating temperature (T-T)	0 - 50 °C
Latency (1 Gbps) Latency (10 Gbps)	2.28 μs 2.39 μs	Storage temperature (T-T)	-20 - 70 °C
Jumbo frames support	✓	Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 90% 0 - 95%
Jumbo frames	12000	Operating altitude	0 - 3000 m
Packet buffer memory	32 MB	Non-operating altitude	0 - 3000 m
Security		Weight & dimensions	
DHCP features	DHCP Option 150, DHCP Option 66, DHCP Option 67, DHCP relay, DHCP server, DHCP snooping	Width Depth	220 mm 400 mm
Access Control List (ACL)	✓	Height	43.2 mm
Access Control List (ACL) egress	1023	Weight	4.05 kg
Access Control List (ACL) ingress	511	Packaging content	
IGMP snooping	✓	Cables included	AC, USB Type-C
IGMP proxy	✓	Quick start guide	✓
MAC address filtering	✓	Rack mount kit	✓
Static port security	✓	Packaging data	
Loop protection	✓	Included power plug types	EU, UK, NA
BPDU filtering/protection	✓	Sustainability	
Authentication	Guest VLAN, MAC-based authentication	Sustainability compliance	✓
Root protection	✓	Certificates	
Password protection	✓	Constitution of the state of	BSMI, CCC, CE, Federal
DoS attack prevention	✓	Compliance certificates	Communications Commission (FCC), Low Voltage Directive (LVD)





606449161472

0606449161472

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.