

NETGEAR M4350-12X12F Hallittu L3 10G Ethernet (100/1000/10000) 1U musta

Tuotemerkki : NETGEAR

Tuotekoodi: XSM4324-100NES

Tuotteen nimi : M4350-12X12F

NETGEAR M4350-12X12F. Kytin tyyppi: Hallittu, Kytinkerros: L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: 10G Ethernet (100/1000/10000), Basic kytin RJ-45 Ethernet-porttien määrä: 12. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytin kapasiteetti: 480 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Qav, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE....
Virtaliitin: AC-in-liitin. Telineasennus, Kotelo: 1U



Management features		Security	
Switch type *	Managed	Authentication type	RADIUS, TACACS+
Switch layer	L3	Queue scheduling algorithms	Strict Priority Queue (SPQ), Weighted random early detection (WRED)
Quality of Service (QoS) support	✓	Multicast features	
Web-based management	✓	Multicast support	✓
ARP inspection	✓	Multicast Listener Discovery (MLD) snooping	✓
Ports & interfaces		Protocols	
Basic switching RJ-45 Ethernet ports quantity *	12	Management protocols	SNMP V1, V2, V3
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	GARP VLAN Registration Protocol (GVRP)	✓
10G Ethernet (copper) ports quantity	12	Routing protocols	OSPF, OSPFv2, OSPFv3, RIP, RIP-1, RIP-2
SFP+ module slots quantity	12	Design	
Power connector	AC-in jack	Rack mounting *	✓
Network		Stackable *	✓
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Qav, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ak, IEEE 802.3bz, IEEE 802.3u	Form factor	1U
10G support *	✓	Product colour	Black
Full duplex	✓	LED indicators	✓
Policy-based routing	✓	Airflow direction	Front-to-back airflow
Flow control support	✓	Performance	
Link aggregation	✓	Built-in processor	✓
Broadcast storm control	✓	Processor model	ARM Cortex-A57
Rate limiting	✓	Processor frequency	1800 MHz
Spanning tree protocol	✓	Memory type	DDR4-SDRAM
6to4 tunnel	✓	Internal memory	2048 MB
IPv4 routes	512	Flash memory	512 MB
IPv6 routes	256	sFlow	✓
VLAN support	✓	Power	
Virtual LAN features	MAC address-based VLAN, Private VLAN, Voice VLAN	Power source *	AC
		Power supply included *	✓
		Power consumption (typical)	95.8 W

Network		Power over Ethernet (PoE)	
Number of VLANs	4093	Power over Ethernet (PoE) *	✗
Data transmission		Other features	
Switching capacity *	480 Gbit/s	Power supply	240 W
Throughput	357.12 Mpps	Operational conditions	
MAC address table *	16000 entries	Operating temperature (T-T)	0 - 50 °C
Store-and-forward	✓	Storage temperature (T-T)	-20 - 70 °C
Latency (1 Gbps)	2.14 µs	Operating relative humidity (H-H)	0 - 90%
Latency (10 Gbps)	2.29 µs	Storage relative humidity (H-H)	0 - 95%
Jumbo frames support	✓	Operating altitude	0 - 3000 m
Jumbo frames	12000	Non-operating altitude	0 - 3000 m
Packet buffer memory	32 MB	Weight & dimensions	
Security		Width	220 mm
DHCP features	DHCP Option 150, DHCP Option 66, DHCP Option 67, DHCP relay, DHCP server, DHCP snooping	Depth	400 mm
Access Control List (ACL)	✓	Height	43.2 mm
Access Control List (ACL) egress	1023	Weight	4.3 kg
Access Control List (ACL) ingress	511	Packaging content	
IGMP snooping	✓	Cables included	AC, USB Type-C
IGMP proxy	✓	Quick start guide	✓
MAC address filtering	✓	Rack mount kit	✓
Static port security	✓	Packaging data	
Loop protection	✓	Included power plug types	EU, UK, NA
BPDU filtering/protection	✓	Sustainability	
Authentication	Guest VLAN, MAC-based authentication	Sustainability compliance	✓
Root protection	✓	Certificates	
Password protection	✓	Compliance certificates	BSMI, CCC, CE, Federal Communications Commission (FCC), Low Voltage Directive (LVD)
DoS attack prevention	✓		



0606449161458



606449161458

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.