NETGEAR XS728T Hallittu L2+/L3 10G Ethernet (100/1000/10000) musta

Tuotemerkki : NETGEAR

Tuotekoodi: XS728T-100NES

Tuotteen nimi : XS728T

NETGEAR XS728T. Kytkin tyyppi: Hallittu, Kytkinkerros: L2+/L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: 10G Ethernet (100/1000/10000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 24, USB 2.0 - porttien määrä: 1. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 560 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Telineasennus

Management features		Security	
Switch type *	Managed	Security algorithms	802.1x RADIUS
Switch layer	L2+/L3	MAC address filtering	1
Quality of Service (QoS) support	 Image: A start of the start of	Multicast features	
Web-based management	 Image: A start of the start of	Multicast support	1
Ports & interfaces		Protocols	
Basic switching RJ-45 Ethernet ports quantity *	24	Management protocols	SNMP v1, v2c, v3
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Design	
SFP+ module slots quantity	4	Rack mounting *	1
USB 2.0 ports quantity	1	Product colour	Black
Network		LED indicators	Activity, Link, Power
Network		Number of fans	4 fan(s)
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Performance	
		Built-in processor	1
		Processor frequency	800 MHz
		Internal memory	512 MB
10G support *	1	Flash memory	256 MB
Copper ethernet cabling technology	10GBASE-T	Noise level	41.6 dB
Cable types supported	Cat5e, Cat6, Cat6a, Cat7	Mean time between failures (MTBF)	514977 h
Port mirroring	1	Power	
Full duplex	1	AC input voltage	100 - 240 V
IP routing	1	AC input frequency	50 - 60 Hz
Flow control support	1	Power consumption (max)	173.3 W
Link aggregation	✓	Power over Ethernet (PoE)	
Rate limiting	1	Power over Ethernet (PoE) *	×
VLAN support	1	Operational conditions	
Virtual LAN features	Private VLAN, Protocol-based VLAN	Operating temperature (T-T)	0 - 50 °C
Number of VLANs	512	Operating relative humidity (H-H)	0 - 90%
Data transmission		Operating altitude	0 - 3000 m
Switching capacity *	560 Gbit/s	Weight & dimensions	
MAC address table *	16000 entries	Width	440 mm
Store-and-forward	1	Depth	310 mm
Latency (10 Gbps)	11.649 µs	Height	43 mm

en -560

Data transmission		Weight & dimensions	
Number of queues	8 128	Weight	5.04 kg
Number of static routes		Packaging content	
Jumbo frames support	1	Cables included	AC
,	10000	Quick start guide	1
Packet buffer memory	3 MB	Rack mount kit	 Image: A set of the set of the
Security		Certificates	
DHCP features	DHCP server, DHCP client	certificates	
Access Control List (ACL)	✓	Certification	CE, FCC CI. A, VCCI CI. A, CI. A EN 55022 (CISPR 22), CI. A C-Tick, EN
Access Control List (ACL) rules	164		55024, CCC
IGMP snooping	✓	Logistics data	
		Harmonized System (HS) code	85176990





606449107241

0606449107241

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.