

## NETGEAR XS508M Hallitsematon 10G Ethernet (100/1000/10000) Harmaa, Hopea



**Tuotemerkki :** NETGEAR

**Tuotekoodi:** XS508M-100EUS

**Tuotteen nimi :** XS508M

NETGEAR XS508M. Kytin tyyppi: Hallitsematon. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: 10G Ethernet (100/1000/10000). MAC-osoitetaulukko: 2000 entries, Kytentäkapasiteetti: 160 Gbit/s. Verkkostandardit: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3aq, IEEE 802.3az,.... Virtaliitin: DC-tulo jakkiliitin. Telineasennus

<b>Management features</b>		<b>Power</b>	
Switch type *	Unmanaged	Power source *	AC
Quality of Service (QoS) support	✓	AC input voltage	100 - 240 V
<b>Ports &amp; interfaces</b>		AC input frequency	50 - 60 Hz
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Input current	1.5 A
Gigabit Ethernet (copper) ports quantity	7	Power consumption (typical)	21.31 W
SFP+ module slots quantity	1	Power consumption (max)	39 W
Power connector	DC-in jack	<b>Operational conditions</b>	
<b>Network</b>		Operating temperature (T-T)	0 - 50 °C
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ae, IEEE 802.3an, IEEE 802.3aq, IEEE 802.3az, IEEE 802.3bz, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Storage temperature (T-T)	-20 - 70 °C
10G support *	✓	Operating relative humidity (H-H)	0 - 95%
<b>Data transmission</b>		Storage relative humidity (H-H)	0 - 95%
Switching capacity *	160 Gbit/s	Operating altitude	0 - 3000 m
MAC address table *	2000 entries	Heat dissipation	147.86 BTU/h
Jumbo frames support	✓	<b>Weight &amp; dimensions</b>	
Jumbo frames	9000	Width	328 mm
<b>Design</b>		Depth	169 mm
Rack mounting *	✓	Height	43.2 mm
Product colour	Grey, Silver	Weight	1.49 kg
LED indicators	✓	<b>Certificates</b>	
Safety	CE: CB 60950-1, LVD 60950-1, AUS/NZ: AS/NZS 60950-1, USA: UL 60950-1, SNE VA, BSMI	Certification	47 CFR FCC, ICES-003:2016 Issue 6, ANSI C63.4:2014, EN 55032:2012+AC2013, EN 55024:2010, EN 61000-3-2:2014, EN 6100-3-3:2013, AS/NZS CISPR 32:2015, VCCI V-3/2015.04, V-4/2012.4, CNS 13438
<b>Performance</b>		<b>Logistics data</b>	
Mean time between failures (MTBF)	1145157 h	Harmonized System (HS) code	85176990



0606449131116



606449131116

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.