

## NETGEAR M4350-36X4V Hallittu L3 10G Ethernet (100/1000/10000) Power over Ethernet -tuki 1U musta

**Tuotemerkki :** NETGEAR

**Tuotekoodi:** XSM4340CV-100NES

**Tuotteen nimi :** M4350-36X4V

NETGEAR M4350-36X4V. Kytin tyyppi: Hallittu, Kytinkerros: L3. Peruskytkentä RJ-45 Ethernet-porttien tyyppi: 10G Ethernet (100/1000/10000), Basic kytkentä RJ-45 Ethernet-porttien määrä: 36. Täysin kaksipuolinen. MAC-osoitetaulukko: 16000 entries, Kytkentäkapasiteetti: 920 Gbit/s. Verkkostandardit: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Qav, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE....  
Virtaliitin: AC-in-liitin. Power over Ethernet -tuki. Telineasennus, Kotelo: 1U



Management features		Multicast features	
Switch type *	Managed	Multicast Listener Discovery (MLD) snooping	✓
Switch layer	L3		
Quality of Service (QoS) support	✓	Protocols	
Web-based management	✓	Management protocols	SNMP V1, V2, V3
ARP inspection	✓	GARP VLAN Registration Protocol (GVRP)	✓
Ports & interfaces		Routing protocols	OSPF, OSPFv2, OSPFv3, RIP, RIP-1, RIP-2
Basic switching RJ-45 Ethernet ports quantity *	36	Design	
Basic switching RJ-45 Ethernet ports type *	10G Ethernet (100/1000/10000)	Rack mounting *	✓
10G Ethernet (copper) ports quantity	36	Stackable *	✓
SFP28 ports quantity	4	Form factor	1U
Power connector	AC-in jack	Product colour	Black
Network		LED indicators	✓
		Airflow direction	Front-to-back airflow
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1Qav, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ak, IEEE 802.3bz, IEEE 802.3u	Performance	
10G support *	✓	Built-in processor	✓
Full duplex	✓	Processor model	ARM Cortex-A57
Policy-based routing	✓	Processor frequency	1800 MHz
Flow control support	✓	Memory type	DDR4-SDRAM
Link aggregation	✓	Internal memory	4096 MB
Broadcast storm control	✓	Flash memory	512 MB
Rate limiting	✓	Noise level	54 dB
Spanning tree protocol	✓	sFlow	✓
6to4 tunnel	✓	Power	
IPv4 routes	512	Power source *	AC
IPv6 routes	256	Power supply included *	✓
VLAN support	✓	AC input voltage	100 - 240 V
		AC input frequency	60 Hz
		Power consumption (typical)	148 W
		Power consumption (max)	454 W

Network		Power over Ethernet (PoE)	
Virtual LAN features	MAC address-based VLAN, Private VLAN, Voice VLAN	Power over Ethernet (PoE) *	✓
Number of VLANs	4093	Power over Ethernet 4PPoE (PoE++) ports quantity	36
Data transmission		Power over Ethernet (PoE) power per port	90 W
Switching capacity *	920 Gbit/s	Total Power over Ethernet (PoE) budget	1760 W
Throughput	684.48 Mpps	Other features	
MAC address table *	16000 entries	Power supply	750 W
Store-and-forward	✓	Operational conditions	
Latency (1 Gbps)	2.54 µs	Operating temperature (T-T)	0 - 45 °C
Latency (10 Gbps)	2.75 µs	Storage temperature (T-T)	-20 - 70 °C
Jumbo frames support	✓	Operating relative humidity (H-H)	0 - 90%
Jumbo frames	12000	Storage relative humidity (H-H)	0 - 95%
Packet buffer memory	64 MB	Operating altitude	0 - 3000 m
Security		Non-operating altitude	0 - 3000 m
DHCP features	DHCP Option 150, DHCP Option 66, DHCP Option 67, DHCP relay, DHCP server, DHCP snooping	Weight & dimensions	
Access Control List (ACL)	✓	Width	440 mm
Access Control List (ACL) egress	1023	Depth	400 mm
Access Control List (ACL) ingress	511	Height	43.2 mm
IGMP snooping	✓	Weight	7.33 kg
IGMP proxy	✓	Packaging content	
MAC address filtering	✓	Cables included	AC, USB Type-C
Static port security	✓	User guide	✓
Loop protection	✓	Rack mount kit	✓
BPDU filtering/protection	✓	Packaging data	
Authentication	Guest VLAN, MAC-based authentication	Included power plug types	EU, NA, UK
Root protection	✓	Sustainability	
Password protection	✓	Sustainability compliance	✓
DoS attack prevention	✓	Certificates	
Authentication type	RADIUS, TACACS+	Compliance certificates	BSMI, CCC, CE, Federal Communications Commission (FCC), Low Voltage Directive (LVD)
Queue scheduling algorithms	Strict Priority Queue (SPQ), Weighted random early detection (WRED)		
Multicast features			
Multicast support	✓		



0606449165104



606449165104

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.