NETGEAR

NETGEAR 48-Port 10G Ethernet Smart Switch (XS748T)

Brand : NETGEAR

Management features

Switch type *

Product code: XS748T-100NES



Product name : 48-Port 10G Ethernet Smart Switch (XS748T)

ProSAFE XS748T - 44 x 10GBASE-T copper ports, 4x SFP+ 1000/10GBASE-X fiber ports, 262.8W max., 47.8 dB, 2.61 kg

NETGEAR 48-Port 10G Ethernet Smart Switch (XS748T). Switch type: Managed, Switch layer: L2+/L3. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 44, USB 2.0 ports quantity: 1. Full duplex. MAC address table: 16000 entries, Switching capacity: 960 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE.... Rack mounting

Managed

Security	
Security algorithms	802.1x RADIUS
MAC address filtering	1
Multicast features	

43 mm

Switch layer L2+/L3 Quality of Service (QoS) support 1 Multicast features Web-based management 1 Multicast support 1 Ports & interfaces Protocols Basic switching RJ-45 Ethernet ports 44 Management protocols SNMP v1, v2c, v3 quantity Basic switching RJ-45 Ethernet ports 10G Ethernet (100/1000/10000) Design type ³ Rack mounting * 1 SFP+ module slots quantity 4 Product colour Black USB 2.0 ports quantity 1 LED indicators Activity, Link, Power Network Number of fans 4 fan(s) IEEE 802.1D, IEEE 802.1Q, IEEE Performance 802.1ab, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE Built-in processor Networking standards * 802.3, IEEE 802.3ad, IEEE 802.3ae, Processor frequency 800 MHz IEEE 802.3an, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z Internal memory 512 MB 10G support * Flash memory 256 MB Copper ethernet cabling technology 10GBASE-T Noise level 47.8 dB Mean time between failures (MTBF) 483808 h Cable types supported Cat5e, Cat6, Cat6a, Cat7 Port mirroring 1 Power Full duplex 1 AC input voltage 100 - 240 V IP routing AC input frequency 50 - 60 Hz Power consumption (max) 262.8 W Flow control support Link aggregation Power over Ethernet (PoE) Rate limiting Power over Ethernet (PoE) * × VLAN support **Operational conditions** Virtual LAN features Private VLAN, Protocol-based VLAN Operating temperature (T-T) 0 - 50 °C Number of VLANs 512 Operating relative humidity (H-H) 0 - 90% Data transmission Operating altitude 0 - 3000 m Switching capacity * 960 Gbit/s Weight & dimensions MAC address table * 16000 entries Width 440 mm Store-and-forward 1 Depth 310 mm Latency (10 Gbps) 3.674 µs

Height

Data transmission		Weight & dimensions	
Number of queues	8	Weight	6.25 kg
Number of static routes	64	Packaging content	
Jumbo frames support	<i>✓</i>	Cables included	AC
Jumbo frames 10000 Packet buffer memory 3 MB		Quick start guide	 Image: A second s
	Rack mount kit	 Image: A second s	
Security		Certificates	
DHCP features Access Control List (ACL) Access Control List (ACL) rules	DHCP server, DHCP client ✓ 164	Certification	CE, FCC CI. A, VCCI CI. A, CI. A EN 55022 (CISPR 22), CI. A C-Tick, EN 55024, CCC
IGMP snooping 🖌	4	Logistics data	
		Harmonized System (HS) code	85176990





606449112382

0606449112382

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.