## Lenovo ThinkSystem ST650 V3 palvelin Teline ( 4U ) Intel $\mbox{ Neon}\mbox{ Bold 5415+ 2,9 GHz 32 GB DDR5-SDRAM 1100 W}$



Tuotemerkki : Lenovo

Tuoteperhe: ThinkSystem

Tuotekoodi: 7D7AA01CEA

Tuotteen nimi : ST650 V3

Lenovo ThinkSystem ST650 V3. Suoritinperhe: Intel® Xeon® Gold, Prosessorin taajuus: 2,9 GHz, Prosessorimalli: 5415+. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: DDR5-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 32 GB. Ethernet LAN, Kaapelitekniikka: 10/100/1000Base-T(X). Virtalähde: 1100 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Teline ( 4U )

| Processor   |   | Design  |   |
|---|---|---|---|
| Processor manufacturer *<br>Processor family *  | Intel<br>Intel® Xeon® Gold                    | Product colour<br>Rack mounting                       | Black<br>✔  |
| Processor generation<br>Processor model *   | Intel Xeon Scalable 4th Gen<br>5415+          | Redundant fans support                                | 1   |
| Processor frequency *   | 2.9 GHz                                       | Performance   |   |
| Processor boost frequency   | 4.1 GHz                                       | Performance management                                | XClarity Controller Platinum  |
| Processor cores   | 8   | Trusted Platform Module (TPM)                         | <ul> <li>Image: A start of the start of</li></ul> |
| Processor cache   | 22.5 MB<br>1                                  | Trusted Platform Module (TPM)<br>version              | 2.0   |
| Number of processors installed  | 1   | Software  |   |
| Memory  | 22.02   | Operating system installed *                          | ×   |
| Internal memory *<br>Internal memory type *<br>ECC<br>Memory layout (slots x size)<br>Maximum internal memory * | 32 GB<br>DDR5-SDRAM<br>✓<br>1 x 32 GB<br>4 TB | Compatible operating systems *                        | Microsoft Windows Server 2019<br>Microsoft Windows Server 2022 Red<br>Hat Enterprise Linux 8.6 Red Hat<br>Enterprise Linux 8.7 Red Hat<br>Enterprise Linux 9.0 Red Hat<br>Enterprise Linux 9.1 SUSE Linux   |
| Storage   |   | Enterprise Server 15 SP4 SUSE                         |   |
| Maximum storage capacity *<br>RAID support *  | 320 ТВ<br>✓                                   |   | Linux Enterprise Server 15 Xen SP4<br>Ubuntu 22.04 LTS 64-bit VMware<br>ESXi 7.0 U3 VMware ESXi 8.0 U1  |
| RAID levels   | 0, 1, 10, JBOD                                | Power   |   |
| Supported RAID controllers  | 9350-8i                                       | Redundant power supply (RPS)                          | 1   |
| Hot-swap  |   | support *   |   |
| Internal drive bays<br>Supported storage drive interfaces   | 8<br>SAS                                      | Power supply *<br>Number of redundant power           | 1100 W  |
|   | JAJ   | supplies installed                                    | 1   |
| Network   | B   | Operational conditions                                |   |
| LAN controller<br>Ethernet LAN  | Broadcom 57416                                | Operating temperature (T-T)                           | 5 - 45 °C   |
| Cabling technology  | 10/100/1000Base-T(X)                          | Storage temperature (T-T)                             | -40 - 60 °C   |
| Ethernet interface type   | 10 Gigabit Ethernet                           | Operating relative humidity (H-H)                     | 8 - 90%   |
| Ports & interfaces  |   | Storage relative humidity (H-H)<br>Operating altitude | 8 - 90%<br>0 - 3050 m   |
| Ethernet LAN (RJ-45) ports *  | 2   |   | 5 5656 m  |
| USB 2.0 ports quantity  | 1   | Weight & dimensions                                   | 175 mm  |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A  | 5   | Width<br>Depth  | 175 mm<br>734 mm  |
| ports quantity<br>VGA (D-Sub) ports quantity  | 1   | Height  | 462 mm  |
| Serial ports quantity   | 1   | Weight  | 39.1 kg   |
| Design  |   | Technical details                                     |   |
| Chassis type *  | Rack (4U)                                     | Supported storage drives form factor (internal)       | 2.5"  |



8032976159828

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.