



Lenovo ThinkSystem ST650 V2 palvelin Tornin (4U) Intel® Xeon Silver 4314 2,4 GHz 32 GB DDR4-SDRAM 750 W

Tuotemerkki : Lenovo

Tuoteperhe: ThinkSystem

Tuotekoodi: 7Z74A033EA

Tuotteen nimi : ST650 V2



Lenovo ThinkSystem ST650 V2. Suoritinperhe: Intel® Xeon Silver, Prosessorin taajuus: 2,4 GHz, Prosessorimalli: 4314. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: DDR4-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 32 GB. Ethernet LAN, Kaapelitekniikka: 10/100/1000Base-T(X). Virtalähde: 750 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Tornin (4U)

Processor		Design	
Processor manufacturer *	Intel	Chassis type *	Tower (4U)
Processor family *	Intel Xeon Silver	Product colour	Black
Processor model *	4314	Rack mounting	✓
Processor frequency *	2.4 GHz		
Processor boost frequency	3.4 GHz		
Processor cache	24 MB		
Number of processors installed	1		
Memory		Performance	
Internal memory *	32 GB	Performance management	XClarity Enterprise
Internal memory type *	DDR4-SDRAM	Trusted Platform Module (TPM)	✓
Memory clock speed	3200 MHz	Trusted Platform Module (TPM) version	2.0
Memory layout (slots x size)	1 x 32 GB		
Storage		Software	
RAID support *	✓	Operating system installed *	✗
RAID levels	0, 1, 5, 6, 10, 50, 60	Compatible operating systems *	Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi
Supported RAID controllers	9350-8i		
Internal drive bays	8		
Graphics		Power	
Maximum graphics card memory	16 MB	Redundant power supply (RPS) support *	✓
		Power supply *	750 W
Network		Number of redundant power supplies installed	1
LAN controller	Broadcom 57416	Operational conditions	
Ethernet LAN	✓	Operating temperature (T-T)	5 - 45 °C
Cabling technology	10/100/1000Base-T(X)	Storage temperature (T-T)	-40 - 60 °C
Ethernet interface type	10 Gigabit Ethernet	Operating relative humidity (H-H)	8 - 90%
		Storage relative humidity (H-H)	8 - 90%
		Operating altitude	0 - 3050 m
Ports & interfaces		Weight & dimensions	
Ethernet LAN (RJ-45) ports *	3	Width	175 mm
USB 2.0 ports quantity	1	Depth	734 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	5	Height	462 mm
VGA (D-Sub) ports quantity	1		
Serial ports quantity	1		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.