



Lenovo ThinkSystem ST650 V2 palvelin Tornin (4U) Intel® Xeon Silver 4310 2,1 GHz 32 GB DDR4-SDRAM 1100 W

Tuotemerkki : Lenovo

Tuoteperhe: ThinkSystem

Tuotekoodi: 7Z74A03TEA

Tuotteen nimi : ST650 V2



Lenovo ThinkSystem ST650 V2. Suoritinperhe: Intel® Xeon Silver, Prosessorin taajuus: 2,1 GHz, Prosessorimalli: 4310. Sisäinen muisti: 32 GB, Sisäisen muistin tyyppi: DDR4-SDRAM, Muistin sijoittelu (paikat x koko): 1 x 32 GB. Ethernet LAN, Kaapelitekniikka: 10/100/1000Base-T(X). Virtalähde: 1100 W, Vikasietoisen virtalähteen tuki (RPS). Alustatyyppi: Tornin (4U)

| Processor | | Ports & interfaces | |
|---|------------------------|--|---|
| Processor manufacturer * | Intel | Serial ports quantity | 1 |
| Processor family * | Intel Xeon Silver | Design | |
| Processor model * | 4310 | Chassis type * | Tower (4U) |
| Processor frequency * | 2.1 GHz | Product colour | Black |
| Processor boost frequency | 3.3 GHz | Rack mounting | ✓ |
| Processor cache | 18 MB | Performance | |
| Number of processors installed | 1 | Performance management | XClarity Enterprise |
| Memory | | Trusted Platform Module (TPM) | ✓ |
| Internal memory * | 32 GB | Trusted Platform Module (TPM) version | 2.0 |
| Internal memory type * | DDR4-SDRAM | Software | |
| Memory clock speed | 3200 MHz | Operating system installed * | ✗ |
| Memory layout (slots x size) | 1 x 32 GB | Compatible operating systems * | Microsoft Windows Server, Red Hat Enterprise Linux, SUSE Linux Enterprise Server, VMware ESXi |
| Storage | | Power | |
| RAID support * | ✓ | Redundant power supply (RPS) support * | ✓ |
| RAID levels | 0, 1, 5, 6, 10, 50, 60 | Power supply * | 1100 W |
| Supported RAID controllers | 930-8i 2GB | Operational conditions | |
| Internal drive bays | 8 | Operating temperature (T-T) | 5 - 45 °C |
| Graphics | | Storage temperature (T-T) | -40 - 60 °C |
| Maximum graphics card memory | 16 MB | Operating relative humidity (H-H) | 8 - 90% |
| Network | | Storage relative humidity (H-H) | 8 - 90% |
| LAN controller | Broadcom 57416 | Operating altitude | 0 - 3050 m |
| Ethernet LAN | ✓ | Weight & dimensions | |
| Cabling technology | 10/100/1000Base-T(X) | Width | 175 mm |
| Ethernet interface type | 10 Gigabit Ethernet | Depth | 734 mm |
| Ports & interfaces | | Height | 462 mm |
| Ethernet LAN (RJ-45) ports * | 3 | | |
| USB 2.0 ports quantity | 1 | | |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 5 | | |
| VGA (D-Sub) ports quantity | 1 | | |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.