

SilverNet BASE 500-90 Verkkosilta 500 Mbit/s Valkoinen

Tuotemerkki : SilverNet

Tuotekoodi: SIL BASE 500-90

Tuotteen nimi : BASE 500-90

SilverNet BASE 500-90. Tiedonsiirron enimmäisnopeus: 500 Mbit/s, Suurin siirtoetäisyys: 6000 m, Tuettu tiedonsiirtonopeus: 500Mbps. Antennin muotoilu: Sisäinen, Antennin vahvistustaso (maks.): 13 dBi, Panoroinnin/kallistusakselin alue: 180°. Wi-Fi-taajuus: Yksikaistainen (5 GHz), Wi-Fi-standardi: Wi-Fi 5 (802.11ac), WLAN-tiedonsiirtonopeus (maks.): 867 Mbit/s. Ethernet LAN -käyttöliittymän tyyppi: Gigabit Ethernet, Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x, IEEE 802.3af. Yhteysteknologia: Langallinen & langaton



| Data transmission | | Features | |
|-------------------------------|---|------------------------------------|---|
| Maximum data transfer rate * | 500 Mbit/s | International Protection (IP) code | IP67 |
| Maximum transfer distance | 6000 m | Surge protection | ✓ |
| Supported data transfer rates | 500Mbps | Quality of Service (QoS) support | ✓ |
| Antenna | | Network Time Protocol (NTP) client | ✓ |
| Antenna design | Internal | Mean time between failures (MTBF) | 60000 h |
| Antenna gain level (max) | 13 dBi | System requirements | |
| Pan/tilt-axis range | 180° | Minimum system requirements | Internet Explorer, Google Chrome, Mozilla Firefox |
| Antennas quantity | 1 | Compatible operating systems | Microsoft Windows, Mac OS, Linux Distributions |
| Wireless LAN features | | Power | |
| Wi-Fi | ✓ | Power source type | PoE |
| Wi-Fi band | Single-band (5 GHz) | AC input voltage | 100-240 V |
| Top Wi-Fi standard | Wi-Fi 5 (802.11ac) | Power supply | 15.4 W |
| WLAN data transfer rate (max) | 867 Mbit/s | DC input voltage | 24 - 48 V |
| Frequency band | 5.1 - 5.8 GHz | Power consumption (typical) | 6 W |
| Transmission gain | 0 - 13 dB | Power consumption (max) | 16 W |
| Signal strength | -40 dBm | Power over Ethernet (PoE) | ✓ |
| Channels quantity | 25 channels | Power over Ethernet (PoE) voltage | 48 V |
| Modulation | 16-QAM, 64-QAM, 256-QAM, BPSK, QPSK | Power plug type | Type G |
| Receiver sensitivity | -82dBm@54Mbps, -74dBm@300Mbps, -68dBm@1.3Gbps | Operational conditions | |
| Output power (dBm) | 26 | Operating temperature (T-T) | -20 - 70 °C |
| Indoor range | 6000m | Operating temperature (T-T) | -4 - 158 °F |
| Outdoor range | 6000m | Operating relative humidity (H-H) | 0 - 95% |
| Network | | Storage temperature (T-T) | -40 - 90 °C |
| Ethernet LAN | ✓ | Storage relative humidity (H-H) | 0 - 95% |
| Ethernet LAN interface type | Gigabit Ethernet | | |

| | | | |
|---|---|--------------------------------|---|
| Network | | Certificates | |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | Certification | CE, FCC |
| Networking standards | IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x, IEEE 802.3af | Weight & dimensions | |
| Cabling technology | 10/100/1000Base-T(X) | Antenna diameter | 48 cm |
| Full duplex | ✓ | Width | 450 mm |
| Auto MDI/MDI-X | ✓ | Depth | 170 mm |
| Static IP | ✓ | Height | 65 mm |
| Dynamic IP | ✓ | Weight | 2.3 kg |
| Ports & interfaces | | Packaging content | |
| Connectivity technology | Wired & Wireless | Packaging content | Includes 1 x radio, 1 x PoE injector PSU and 1 x Tilt and Swivel 3 Axis mounting bracket. |
| Ethernet LAN (RJ-45) ports | 1 | Grounding | ✓ |
| Security | | PoE+ Injector(s) | ✓ |
| Security algorithms | 256-bit AES, SNMP, SNMPv2, SSH | Mounting bracket(s) included | ✓ |
| Security features | 802.1x, 802.11i, 802.1Q | Power supply included | ✓ |
| MAC address filtering | ✓ | Antenna included | ✓ |
| Authentication method | WPA2 AES | Quick installation guide | ✓ |
| Management features | | Packaging data | |
| Management platform | SNMP V2 | Package width | 215 mm |
| Web-based management | ✓ | Package depth | 605 mm |
| DHCP client | ✓ | Package height | 140 mm |
| Features | | Package weight | 2.91 kg |
| Product type * | Network bridge | Package type | Box |
| Product colour | White | Quantity per pack | 1 pc(s) |
| Remote control function | ✓ | Logistics data | |
| LED indicators | LAN, Signal strength | UK Trade Tariff code | 85176200 |
| Automatic Transmit Power Control (ATPC) | ✓ | Country of origin | United Kingdom |
| Wall mountable | ✓ | | |
| Reset button | ✓ | | |



5060693980213

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-DEC-2024. Prints or copies of Information are only valid on the printed Publication date