

SilverNet Base 500 Network bridge 500 Mbit/s White

Brand : SilverNet

Product code: SIL BASE 500

Product name : Base 500

Multipoint base, up to 500 Mbps with 2 x N-type connectors for external antenna

[SilverNet Base 500 Network bridge 500 Mbit/s White:](#)

The SIL BASE 500 is a Multipoint receiver with 2 external antenna connectors. It can be used in a multipoint system or as a long range Point to Point link. The SIL BASE 500 is capable of up to 500Mbps up to 5km (depending on which external antenna is fitted).

When fitted with a Dual polarised Omni or Sector antenna the SIL BASE 500 can be used as a Multipoint receiver, receiving signals from multiple clients at the same time.

The SIL BASE 500 can also be used as a long range Backhaul link when fitted with Dish or Grid antennas.

Please see our Antenna Datasheet for available antennas.



Data transmission		Features	
Maximum data transfer rate *	500 Mbit/s	Quality of Service (QoS) support	✓
Supported data transfer rates	95, 240, 500Mbps	Wi-Fi Multimedia (WMM)/(WME)	✓
Antenna		Network Time Protocol (NTP) client	✓
Antenna design	External	Mean time between failures (MTBF)	60000 h
Antenna connector type	N-type	System requirements	
Antennas quantity	1	Minimum system requirements	Internet Explorer, Google Chrome, Mozilla Firefox
Wireless LAN features		Compatible operating systems	Microsoft Windows, Mac OS, Linux Distributions
Wi-Fi	✓	Power	
Wi-Fi band	Single-band (5 GHz)	Power source type	DC, PoE
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)	AC input voltage	100 - 240 V
WLAN data transfer rate (max)	867 Mbit/s	Power supply	15.4 W
Frequency band	5.1 - 5.8 GHz	DC input voltage	24 - 48 V
Modulation	16-QAM, 64-QAM, 256-QAM, BPSK, QPSK	Power consumption (typical)	6 W
Receiver sensitivity	-82dBm@54Mbps, -74dBm@300Mbps, -68dBm@1.3Gbps	Power consumption (max)	16 W
Output power (dBm)	26	Power over Ethernet (PoE)	✓
Indoor range	5.1GHz - 5.7GHz	Power over Ethernet (PoE) voltage	48 V
Outdoor range	5.4GHz - 5.8GHz	Power plug type	Type G
Network		Operational conditions	
Ethernet LAN	✓	Operating temperature (T-T)	-20 - 70 °C
Ethernet LAN interface type	Gigabit Ethernet	Operating temperature (T-T)	-4 - 158 °F
Ethernet LAN data rates	10,100,1000 Mbit/s	Operating relative humidity (H-H)	0 - 95%
Networking standards	IEEE 802.11i, IEEE 802.1Q, IEEE 802.1x	Storage temperature (T-T)	-40 - 90 °C
Cabling technology	10/100/1000Base-T(X)	Storage relative humidity (H-H)	0 - 95%
Full duplex	✓	Certificates	
		Certification	CE, FCC

Network		Weight & dimensions	
Auto MDI/MDI-X	✓	Width	220 mm
Static IP	✓	Depth	75 mm
Dynamic IP	✓	Height	220 mm
		Weight	1.6 kg
Ports & interfaces		Packaging content	
Connectivity technology	Wired & Wireless	Packaging content	Includes 1 x radio, 1 x PoE injector PSU and 1 x Tilt and Swivel 3 Axis mounting bracket.
Ethernet LAN (RJ-45) ports	1	Grounding	✓
Security		PoE+ Injector(s)	✓
Security algorithms	256-bit AES, SNMPv2	Mounting bracket(s) included	✓
Security features	802.1x, 802.11i, 802.1Q	Power supply included	✓
MAC address filtering	✓	Quick installation guide	✓
Authentication method	WPA2 AES	Packaging data	
Management features		Package width	307 mm
Management platform	SNMP V2	Package depth	395 mm
Web-based management	✓	Package height	102 mm
DHCP client	✓	Package weight	2.59 kg
Features		Package type	Box
Product type *	Network bridge	Quantity per pack	1 pc(s)
Product colour	White	Logistics data	
Remote control function	✓	UK Trade Tariff code	85176200
LED indicators	LAN, Signal strength	Country of origin	United Kingdom
Automatic Transmit Power Control (ATPC)	✓		
Wall mountable	✓		
Reset button	✓		
International Protection (IP) code	IP67		
Surge protection	✓		



5060693980206

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.