

SilverNet Base 500 Verkkosilta 500 Mbit/s Valkoinen

Tuotemerkki : SilverNet

Tuotekoodi: SIL BASE 500

Tuotteen nimi : Base 500

SilverNet Base 500. Tiedonsiirron enimmäisnopeus: 500 Mbit/s, Tuettu tiedonsiirtonopeus: 95, 240, 500Mbps. Antennin muotoilu: Ulkoinen, Antenniliittimen tyyppi: N-tyyppi. Wi-Fi-taajuus: Yksikaistainen (5 GHz), Wi-Fi-standardi: Wi-Fi 5 (802.11ac), WLAN-tiedonsiirtonopeus (maks.): 867 Mbit/s. Ethernet LAN -käyttöliittymän tyyppi: Gigabitti Ethernet, Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 802.11i, IEEE 802.1Q, IEEE 802.1x. Yhteysteknologia: Langallinen & langaton



| Data transmission | | Features | |
|-------------------------------|---|------------------------------------|---|
| Maximum data transfer rate * | 500 Mbit/s | Quality of Service (QoS) support | ✓ |
| Supported data transfer rates | 95, 240, 500Mbps | Wi-Fi Multimedia (WMM)/(WME) | ✓ |
| Antenna | | Network Time Protocol (NTP) client | ✓ |
| Antenna design | External | Mean time between failures (MTBF) | 60000 h |
| Antenna connector type | N-type | System requirements | |
| Antennas quantity | 1 | Minimum system requirements | Internet Explorer, Google Chrome, Mozilla Firefox |
| Wireless LAN features | | Compatible operating systems | Microsoft Windows, Mac OS, Linux Distributions |
| Wi-Fi | ✓ | Power | |
| Wi-Fi band | Single-band (5 GHz) | Power source type | DC, PoE |
| Top Wi-Fi standard | Wi-Fi 5 (802.11ac) | AC input voltage | 100 - 240 V |
| WLAN data transfer rate (max) | 867 Mbit/s | Power supply | 15.4 W |
| Frequency band | 5.1 - 5.8 GHz | DC input voltage | 24 - 48 V |
| Modulation | 16-QAM, 64-QAM, 256-QAM, BPSK, QPSK | Power consumption (typical) | 6 W |
| Receiver sensitivity | -82dBm@54Mbps, -74dBm@300Mbps, -68dBm@1.3Gbps | Power consumption (max) | 16 W |
| Output power (dBm) | 26 | Power over Ethernet (PoE) | ✓ |
| Indoor range | 5.1GHz - 5.7GHz | Power over Ethernet (PoE) voltage | 48 V |
| Outdoor range | 5.4GHz - 5.8GHz | Power plug type | Type G |
| Network | | Operational conditions | |
| Ethernet LAN | ✓ | Operating temperature (T-T) | -20 - 70 °C |
| Ethernet LAN interface type | Gigabit Ethernet | Operating temperature (T-T) | -4 - 158 °F |
| Ethernet LAN data rates | 10,100,1000 Mbit/s | Operating relative humidity (H-H) | 0 - 95% |
| Networking standards | IEEE 802.11i, IEEE 802.1Q, IEEE 802.1x | Storage temperature (T-T) | -40 - 90 °C |
| Cabling technology | 10/100/1000Base-T(X) | Storage relative humidity (H-H) | 0 - 95% |
| Full duplex | ✓ | Certificates | |
| | | Certification | CE, FCC |

| Network | | Weight & dimensions | |
|---|-------------------------|------------------------------|---|
| Auto MDI/MDI-X | ✓ | Width | 220 mm |
| Static IP | ✓ | Depth | 75 mm |
| Dynamic IP | ✓ | Height | 220 mm |
| Ports & interfaces | | Weight | 1.6 kg |
| Connectivity technology | Wired & Wireless | Packaging content | |
| Ethernet LAN (RJ-45) ports | 1 | Packaging content | Includes 1 x radio, 1 x PoE injector PSU and 1 x Tilt and Swivel 3 Axis mounting bracket. |
| Security | | Grounding | ✓ |
| Security algorithms | 256-bit AES, SNMPv2 | PoE+ Injector(s) | ✓ |
| Security features | 802.1x, 802.11i, 802.1Q | Mounting bracket(s) included | ✓ |
| MAC address filtering | ✓ | Power supply included | ✓ |
| Authentication method | WPA2 AES | Quick installation guide | ✓ |
| Management features | | Packaging data | |
| Management platform | SNMP V2 | Package width | 307 mm |
| Web-based management | ✓ | Package depth | 395 mm |
| DHCP client | ✓ | Package height | 102 mm |
| Features | | Package weight | 2.59 kg |
| Product type * | Network bridge | Package type | Box |
| Product colour | White | Quantity per pack | 1 pc(s) |
| Remote control function | ✓ | Logistics data | |
| LED indicators | LAN, Signal strength | UK Trade Tariff code | 85176200 |
| Automatic Transmit Power Control (ATPC) | ✓ | Country of origin | United Kingdom |
| Wall mountable | ✓ | | |
| Reset button | ✓ | | |
| International Protection (IP) code | IP67 | | |
| Surge protection | ✓ | | |



5060693980206

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 06-MAR-2025. Prints or copies of Information are only valid on the printed Publication date