

## SilverNet FDD 801G-30-PCP Verkkosilta 1000 Mbit/s Valkoinen

**Tuotemerkki :** SilverNet

**Tuotekoodi:** SIL FDD 801G-30-PCP

**Tuotteen nimi :** FDD 801G-30-PCP

SilverNet FDD 801G-30-PCP. Tiedonsiirron enimmäisnopeus: 1000 Mbit/s, Suurin siirtoetäisyys: 2000 m. Antennin muotoilu: Ulkoinen. WLAN-tiedonsiirtonopeus (maks.): 1000 Mbit/s, Taajuuskaista: 80GHz (71 - 76GHz, 81 - 86GHz), Modulointi: 8-QAM, 16-QAM, 32-QAM, 64-QAM, 128-QAM, 256-QAM, BPSK. Ethernet LAN -käyttöliittymän tyyppi: Gigabit Ethernet, Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 1588v2, IEEE 802.1ad, IEEE 802.1ag, IEEE 802.1p, IEEE 802.3ad, IEEE 802.3x. Yhteysteknologia: Langallinen & langaton



<b>Data transmission</b>		<b>Features</b>	
Maximum data transfer rate *	1000 Mbit/s	Quality of Service (QoS) support	✓
Maximum transfer distance	2000 m	Network Time Protocol (NTP) client	✓
<b>Antenna</b>		Flow control support	✓
Antenna design	External	RMON Statistics	✓
Antennas quantity	2	Link Loss Forwarding (LLF)	✓
<b>Wireless LAN features</b>		Link aggregation	✓
WLAN data transfer rate (max)	1000 Mbit/s	<b>Power</b>	
Frequency band	80GHz (71 - 76GHz, 81 - 86GHz)	Power source type	PoE
Modulation	8-QAM, 16-QAM, 32-QAM, 64-QAM, 128-QAM, 256-QAM, BPSK	AC input voltage	100-240 V
Receiver sensitivity	See Datasheet	Power consumption (typical)	32 W
Output power (dBm)	See Datasheet	Power consumption (max)	53 W
Frequency stability	5 ppm	Power over Ethernet (PoE)	✓
Outdoor range	2000	Power over Ethernet (PoE) voltage	55 V
<b>Network</b>		Power plug type	Type G
Ethernet LAN	✓	<b>Operational conditions</b>	
Ethernet LAN interface type	Gigabit Ethernet	Operating temperature (T-T)	-35 - 55 °C
Ethernet LAN data rates	10,100,1000 Mbit/s	<b>Certificates</b>	
Networking standards	IEEE 1588v2, IEEE 802.1ad, IEEE 802.1ag, IEEE 802.1p, IEEE 802.3ad, IEEE 802.3x	Certification	ETSI EN 302 217 / FCC CFR 47, Part 101 and Part 15
Cabling technology	10/100/1000Base-T(X)	<b>Weight &amp; dimensions</b>	
Full duplex	✓	Antenna diameter	30 cm
Auto MDI/MDI-X	✓	Width	290 mm
Static IP	✓	Depth	302.5 mm
Dynamic IP	✓	Height	117.6 mm
<b>Ports &amp; interfaces</b>		Weight	12.5 kg
Connectivity technology	Wired & Wireless	<b>Packaging content</b>	
Ethernet LAN (RJ-45) ports	2	Grounding	✓
<b>Security</b>		PoE+ Injector(s)	✓
Security algorithms	128-bit AES, 256-bit AES	Mounting bracket(s) included	✓

<b>Security</b>		<b>Packaging content</b>	
MAC address filtering	✓	Power supply included	✓
Access Control List (ACL)	✓	Cables included	LAN (RJ-45)
<b>Management features</b>		Antenna included	✓
Management protocols	SNMP v1/v2c/v3, HTTPs, SSH, SFTP, RADIUS,	Manual	✓
Web-based management	✓	Quick installation guide	✓
<b>Features</b>		<b>Other features</b>	
Product type *	Network bridge	Warranty period	2 year(s)
Mounting type	Pole/Wall	<b>Packaging data</b>	
Product colour	White	Package width	400 mm
Power LED	✓	Package depth	400 mm
Real-Time Parameter Control (RTPC)	✓	Package height	500 mm
Automatic Transmit Power Control (ATPC)	✓	Package weight	1.55 kg
International Protection (IP) code	IP65	Package type	Box
Surge protection	✓	Quantity per pack	1 pc(s)
		<b>Logistics data</b>	
		UK Trade Tariff code	85176200



5060693980831

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.