

SilverNet MAX 95-PCP Verkkosilta 95 Mbit/s Valkoinen

Tuotemerkki : SilverNet

Tuotekoodi: SIL MAX 95-PCP

Tuotteen nimi : MAX 95-PCP

SilverNet MAX 95-PCP. Tiedonsiirron enimmäisnopeus: 95 Mbit/s, Suurin siirtoetäisyys: 60000 m, Tuettu tiedonsiirtonopeus: 95, 240, 500, 1000Mbps. Antennin muotoilu: Sisäinen, Antennin vahvistustaso (maks.): 23 dBi, Panoroinnin/kallistusakselin alue: 180°. Wi-Fi-taajuus: Yksikaistainen (5 GHz), Wi-Fi-standardi: Wi-Fi 5 (802.11ac), WLAN-tiedonsiirtonopeus (maks.): 1300 Mbit/s. Ethernet LAN -käyttöliittymän tyyppi: Gigabitti Ethernet, Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x. Yhteysteknologia: Langallinen & langaton



Data transmission		Features	
Maximum data transfer rate *	95 Mbit/s	International Protection (IP) code	IP67
Maximum transfer distance	60000 m	Surge protection	✓
Supported data transfer rates	95, 240, 500, 1000Mbps	Quality of Service (QoS) support	✓
Antenna		Wi-Fi Multimedia (WMM)/(WME)	✓
Antenna design	Internal	Network Time Protocol (NTP) client	✓
Antenna gain level (max)	23 dBi	Mean time between failures (MTBF)	60000 h
Pan/tilt-axis range	180°	System requirements	
Antennas quantity	1	Minimum system requirements	Internet Explorer, Google Chrome, Mozilla Firefox
Wireless LAN features		Compatible operating systems	Microsoft Windows, Mac OS, Linux Distributions
Wi-Fi	✓	Power	
Wi-Fi band	Single-band (5 GHz)	Power source type	DC, PoE
Top Wi-Fi standard	Wi-Fi 5 (802.11ac)	AC input voltage	100-240 V
WLAN data transfer rate (max)	1300 Mbit/s	Power supply	15.4 W
Frequency band	5.1 - 5.8 GHz	DC input voltage	24-48/48-56 V
Transmission gain	0 - 23 dB	Power consumption (typical)	6 W
Signal strength	-40 dBm	Power consumption (max)	16 W
Channels quantity	25 channels	Power over Ethernet (PoE)	✓
Modulation	16-QAM, 64-QAM, 256-QAM, BPSK, QPSK	Power over Ethernet (PoE) voltage	48 V
Receiver sensitivity	-82dBm@54Mbps, -74dBm@300Mbps, -68dBm@1.3Gbps	Power plug type	Type G
Output power (dBm)	26	Operational conditions	
Indoor range	60000m	Operating temperature (T-T)	-20 - 70 °C
Outdoor range	60000m	Operating temperature (T-T)	-4 - 158 °F
Network		Operating relative humidity (H-H)	0 - 95%
Ethernet LAN	✓	Storage temperature (T-T)	-40 - 90 °C
Ethernet LAN interface type	Gigabit Ethernet	Storage relative humidity (H-H)	0 - 95%
Ethernet LAN data rates	10,100,1000 Mbit/s	Certificates	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11i, IEEE 802.11n, IEEE 802.1Q, IEEE 802.1x	Certification	CE, FCC

Network		Weight & dimensions	
Cabling technology	10/100/1000Base-T(X)	Antenna diameter	51 cm
Full duplex	✓	Width	370 mm
Auto MDI/MDI-X	✓	Depth	370 mm
Static IP	✓	Height	90 mm
Dynamic IP	✓	Weight	2.5 kg
Ports & interfaces		Packaging content	
Connectivity technology	Wired & Wireless	Grounding	✓
Ethernet LAN (RJ-45) ports	1	PoE+ Injector(s)	✓
Power over Ethernet plus (PoE+) ports quantity	1	Mounting bracket(s) included	✓
Security		Power supply included	✓
Security algorithms	256-bit AES, 802.1x RADIUS, SNMPv2, SSH	Antenna included	✓
MAC address filtering	✓	Quick installation guide	✓
Authentication method	WPA2 AES	Packaging data	
Management features		Package width	450 mm
Management protocols	SNMP V2	Package depth	290 mm
Web-based management	✓	Package height	480 mm
DHCP client	✓	Package weight	9.15 kg
Features		Package type	Box
Product type *	Network bridge	Quantity per pack	2 pc(s)
Product colour	White	Logistics data	
Remote control function	✓	UK Trade Tariff code	85176200
LED indicators	LAN, Signal strength	Country of origin	United Kingdom
Automatic Transmit Power Control (ATPC)	✓		
Wall mountable	✓		
Reset button	✓		



5060693980077

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 28-DEC-2024. Prints or copies of Information are only valid on the printed Publication date