SilverNet SIL FDD 805G-60-PCP silta ja toistin Verkkosilta 5000 Mbit/s Valkoinen

Tuotemerkki : SilverNet Tuotekoodi: SIL FDD 805G-60-PCP

Tuotteen nimi: SIL FDD 805G-60-PCP

SilverNet SIL FDD 805G-60-PCP. Tiedonsiirron enimmäisnopeus: 5000 Mbit/s, Suurin siirtoetäisyys: 5000 m. Antennin muotoilu: Ulkoinen. WLAN-tiedonsiirtonopeus (maks.): 10000 Mbit/s, Taajuuskaista: 80GHz (71 - 76GHz, 81 - 86GHz), Modulointi: 8-QAM, 16-QAM, 32-QAM, 64-QAM, 128-QAM, 256-QAM, BPSK. Ethernet LAN -käyttöliittymän tyyppi: Gigabitti Ethernet, Ethernet LAN -datanopeudet: 10,100,1000 Mbit/s, Verkkostandardit: IEEE 1588v2, IEEE 802.1ad, IEEE 802.1ag, IEEE 802.1p, IEEE 802.3ad, IEEE 802.3x. Yhteysteknologia: Langallinen & langaton





Data transmission		Features	
Maximum data transfer rate *	5000 Mbit/s	Network Time Protocol (NTP) client	✓
Maximum transfer distance	5000 m	Flow control support	✓
Antenna		RMON Statistics	✓
Antenna design	External	Link Loss Forwarding (LLF)	✓
Antennas quantity	1	Link aggregation	✓
Wireless LAN features		System requirements	
WLAN data transfer rate (max) Frequency band	10000 Mbit/s 80GHz (71 - 76GHz, 81 - 86GHz)	Minimum system requirements	Internet Explorer, Microsoft Edge, Google Chrome, Mozilla Firefox
Modulation	8-QAM, 16-QAM, 32-QAM, 64-QAM, 128-QAM, 256-QAM, BPSK	Compatible operating systems	Microsoft Windows, Mac OS, Linux Distributions
Receiver sensitivity	See Datasheet	Power	
Output power (dBm)	See Datasheet	Power source type	PoE
Frequency stability Outdoor range	5 ppm 5000	AC input voltage	100-240 V
	3000	Power consumption (typical)	32 W
Network		Power consumption (max)	53 W
Ethernet LAN	✓	Power over Ethernet (PoE)	1
Ethernet LAN interface type	Gigabit Ethernet	Power over Ethernet (PoE) voltage	55 V
Ethernet LAN data rates	10,100,1000 Mbit/s	Power plug type	Type G
Networking standards	IEEE 1588v2, IEEE 802.1ad, IEEE 802.1ag, IEEE 802.1p, IEEE 802.3ad,	Operational conditions	
	IEEE 802.3x	Operating temperature (T-T)	-35 - 55 °C
Cabling technology	10/100/1000Base-T(X)	Certificates	
Full duplex Auto MDI/MDI-X	1	Certification	ETSI EN 302 217 / FCC CFR 47, Part 101 and Part 15
Static IP	✓	Weight & dimensions	
Dynamic IP	✓	Antenna diameter	60 cm
Ports & interfaces		Weight	15.5 kg
Connectivity technology	Wired & Wireless	Packaging content	
Ethernet LAN (RJ-45) ports	4	Grounding	✓
Security		PoE+ Injector(s)	✓
Security algorithms	128-bit AES, 256-bit AES	Mounting bracket(s) included	✓

Security		Packaging content	
MAC address filtering	✓	Power supply included	✓
Access Control List (ACL)	✓	Cables included	LAN (RJ-45)
Management features		Antenna included	✓
Management protocols	SNMP v1/v2c/v3, HTTPs, SSH, SFTP, RADIUS,	Manual	✓
		Quick installation guide	✓
Web-based management	✓	Other features	
Features		Warranty period	2 year(s)
Product type *	Network bridge	Packaging data	
Mounting type	Pole/Wall	Package width	700 mm
Product colour	White	Package depth	700 mm
Power LED	✓	Package height	500 mm
Real-Time Parameter Control (RTPC)	✓	Package weight	18.5 kg
Automatic Transmit Power Control	✓ IP67 ✓	Package type	Box
(ATPC)		Quantity per pack	1 pc(s)
International Protection (IP) code		Logistics data	
Surge protection			05176000
Quality of Service (QoS) support	✓	UK Trade Tariff code	85176200



5060693980893

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.