

SilverNet U2460-PCP Verkkosilta 500 Mbit/s Valkoinen

Tuotemerkki : SilverNet

Tuotekoodi: SIL U2460-PCP

Tuotteen nimi : U2460-PCP

SilverNet U2460-PCP. Tiedonsiirron enimmäisnopeus: 500 Mbit/s, Suurin siirtoetäisyys: 10000 m. Antennin muotoilu: Ulkoinen. Taajuuskaista: 24 GHz, Modulointi: 16-QAM, 32-QAM, 64-QAM, 128-QAM, 512-QAM, 1024-QAM, Vastaanottimen herkkyys: 4 QAM (-88) 16 QAM (-81) 32 QAM (-76.5) 64 QAM (-73.5) 128 QAM (-70.5) 256 QAM (-67) 512 QAM.... Ethernet LAN -käyttöliittymän tyyppi: Gigabitti Ethernet, Ethernet LAN -datanopeudet: 1000 Mbit/s, Verkkostandardit: IEEE 802.11ad, IEEE 802.1p, IEEE 802.3ad, IEEE 802.3x. Yhteysteknologia: Langallinen & langaton

Data transmission		Features	
Maximum data transfer rate *	500 Mbit/s	International Protection (IP) code	IP65
Maximum transfer distance	10000 m	Quality of Service (QoS) support	✓
Antenna		Flow control support	✓
Antenna design	External	RMON Statistics	✓
Antennas quantity	2	Link Loss Forwarding (LLF)	✓
Wireless LAN features		Link aggregation	✗
Frequency band	24 GHz	Power	
Modulation	16-QAM, 32-QAM, 64-QAM, 128-QAM, 512-QAM, 1024-QAM	Power source type	PoE
Receiver sensitivity	4 QAM (-88) 16 QAM (-81) 32 QAM (-76.5) 64 QAM (-73.5) 128 QAM (-70.5) 256 QAM (-67) 512 QAM (-67.5) 1024 QAM (-60.5)	Power consumption (max)	35 W
Output power (dBm)	4 QAM (+21) 16 QAM (+19) 32 QAM (+17) 64 QAM (+17) 128 QAM (+17) 256 QAM (+17) 512 QAM (+17) 1024 QAM (+16)	Power over Ethernet (PoE)	✓
Frequency stability	5 ppm	Power over Ethernet (PoE) voltage	48 V
Network		Operational conditions	
Ethernet LAN	✓	Operating temperature (T-T)	-35 - 55 °C
Ethernet LAN interface type	Gigabit Ethernet	Certificates	
Ethernet LAN data rates	1000 Mbit/s	Certification	ETSI, FCC
Networking standards	IEEE 802.11ad, IEEE 802.1p, IEEE 802.3ad, IEEE 802.3x	Weight & dimensions	
Full duplex	✓	Antenna diameter	60 cm
Static IP	✓	Width	254 mm
Ports & interfaces		Depth	154 mm
Connectivity technology	Wired & Wireless	Height	254 mm
Ethernet LAN (RJ-45) ports	2	Packaging content	
Power over Ethernet plus (PoE+) ports quantity	1	Grounding	✓
I/O ports	2x GE electrical	PoE+ Injector(s)	✓
Management features		Mounting bracket(s) included	✓
Management platform	Web GUI, In Band management, SilverView NMS	Power supply included	✓
Web-based management	✓	Antenna included	✓
Features		Quick installation guide	✓
Product type *	Network bridge	Other features	
Product colour	White	Warranty period	2 year(s)
Remote control function	✓	Packaging data	
Power LED	✓	Package width	700 mm
Real-Time Parameter Control (RTPC)	✓	Package depth	700 mm
		Package height	500 mm
		Package weight	18.5 kg
		Package type	Box
		Quantity per pack	2 pc(s)
		Logistics data	
		UK Trade Tariff code	85176200

Features

- Automatic Transmit Power Control (ATPC) ✓
- VoIP ✓



5060693980763

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.