

TP-Link Tapo C120 IP-turvakamera Sisätila ja ulkotila 2560 x 1440 pikseliä Katto/seinä/työpöytä

Tuotemerkki : TP-Link Tuoteperhe: Tapo Tuotekoodi: TAPO C120

Tuotteen nimi: Tapo C120

TP-Link Tapo C120. Malli: IP-turvakamera, Tuettu sijoitus: Sisätila ja ulkotila, Yhteysteknologia: Langallinen & langaton. Kiinnitystyyppi: Katto/seinä/työpöytä, Tuotteen väri: Valkoinen, musta. Näkökentän kulma: 120°. Anturin tyyppi: CMOS, Optisen sensorin koko: 25,4 / 2,9 mm (1 / 2.9"). Kiinteä polttoväli: 3,17 mm






Performance		Network	
Type * Placement supported * Connectivity technology * Day/night mode	IP security camera Indoor & outdoor Wired & Wireless ✓	Networking standards Wi-Fi * Wi-Fi standards	IEEE 802.11n, IEEE 802.11b, IEEE 802.11g ✓ 802.11b, 802.11g, Wi-Fi 4 (802.11n)
Design		Bluetooth *	X
Mounting type * Product colour * LED indicators	Ceiling/Wall/Desk White, Black ✓	Storage Built-in HDD * Card reader integrated	×
Camera Field of view (FOV) angle	120°	Compatible memory cards Maximum memory card size	MicroSD (TransFlash) 512 GB
Image sensor		Ports & interfaces	
Number of sensors	1	DC-in jack	✓
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")	Security	
Sensor type *	CMOS	Video motion detection	1
Lens system		Security algorithms	WPA, WPA2-PSK
Maximum aperture number 1.65		Management features	
Fixed focal length	3.17 mm	Reset button	✓
Night vision		Power	
Night vision * Night vision distance Colour night vision distance Infra-red wavelength	✓ 10 m 10 m 940 nm	Power source type * AC input voltage AC input frequency DC output voltage	DC 100 - 240 V 50 / 60 Hz 5
Video		DC output current	1 A
Maximum resolution *	- · · · · · · · · · · · · · · · · · · ·	Operational conditions	
Total megapixels * Video formats supported	4 MP H.264	Operating temperature (T-T)	-20 - 45 °C

Video		Operational conditions	
Frame rate	20 fps	Storage temperature (T-T)	-20 - 60 °C
Audio		Operating relative humidity (H-H)	10 - 90%
Built-in speaker(s)	✓	Storage relative humidity (H-H)	5 - 90%
Audio system	2-way	Weight & dimensions	
Signal-to-Noise Ratio (SNR)	96 dB	Width	67.4 mm
Built-in microphone	✓	Depth	57.4 mm
Network		Height	44.1 mm
Ethernet LAN *	×	Packaging content	
		Number of cameras *	1









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.