



ATEN KE6912 KVM -kytkin Lähetin & vastaanotin

Tuotemerkki : ATEN

Tuotekoodi: KE6912-AX-G

Tuotteen nimi : KE6912

ATEN KE6912. Malli: Lähetin & vastaanotin, Yhteysteknologia: Langallinen, Tuetut kaapelityypit: Cat5e. Lähettimen videoportin tyyppi: DVI-D, Lähettimen paikallisen näppäimistön/hiiren porttityyppi: USB. Vastaanottimen paikallisen videoportin tyyppi: DVI-D, Vastaanottimen paikallisen näppäimistön/hiiren porttityyppi: USB. AC-adapterin lähtöjännite: 5 V, Tehonkulutus (lähetin) (max): 12,53 W, Tehonkulutus (vastaanotin) (max): 11,27 W. Lähettimen leveys: 21,5 cm, Lähettimen syvyys: 16,3 cm, Lähettimen korkeus: 4,18 cm



| Features | | Ports & interfaces | |
|--|------------------------|---------------------------------------|-------------|
| Type * | Transmitter & receiver | PC Audio in | ✓ |
| Connectivity technology * | Wired | PC Audio out | ✓ |
| Cable types supported | Cat5e | Power | |
| Rack mounting | ✓ | AC adapter output voltage | 5 V |
| Maximum digital resolution | 2560 x 2048 pixels | Power consumption (transmitter) (max) | 12.53 W |
| On Screen Display (OSD) | ✓ | Power consumption (receiver) (max) | 11.27 W |
| Product colour | Black | Weight & dimensions | |
| Material | Metal | Transmitter width | 21.5 cm |
| LED indicators | ✓ | Transmitter depth | 16.3 cm |
| Certification | RoHS | Transmitter height | 4.18 cm |
| Transmitter | | Transmitter weight | 1.17 kg |
| Transmitter video port type | DVI-D | Receiver width | 22.8 cm |
| Transmitter local keyboard/mouse port type | USB | Receiver depth | 17.2 cm |
| RJ-45 ports quantity (transmitter) | 1 | Receiver height | 5.48 cm |
| Receiver | | Receiver weight | 1.28 kg |
| Receiver local video port type | DVI-D | Packaging content | |
| Receiver local keyboard/mouse port type | USB | AC adapter included | ✓ |
| RJ-45 ports quantity (receiver) | 1 | Cables included | KVM |
| Ports & interfaces | | Manual | ✓ |
| RS-232 ports | 2 | Operational conditions | |
| | | Operating temperature (T-T) | 0 - 50 °C |
| | | Storage temperature (T-T) | -20 - 60 °C |
| | | Operating relative humidity (H-H) | 0 - 95% |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.