ATEN

ATEN KE6912 KVM -kytkin Lähetin & vastaanotin

Tuotemerkki : ATEN Tuotekoodi: KE6912-AX-G

Tuotteen nimi: KE6912

ATEN KE6912. Malli: Lähetin & vastaanotin, Yhteysteknologia: Langallinen, Tuetut kaapelityypit: Cat5e. Lähettimen videoportin tyyppi: DVI-D, Lähettimen paikallisen näppäimistön/hiiren porttityyppi: USB. Vastaanottimen paikallisen videoportin tyyppi: DVI-D, Vastaanottimen paikallisen näppäimistön/hiiren porttityyppi: USB. AC-adapterin lähtöjännite: 5 V, Tehonkulutus (lähetin) (max): 12,53 W, Tehonkulutus (vastaanotin) (max): 11,27 W. Lähettimen leveys: 21,5 cm, Lähettimen syvyys: 16,3 cm, Lähettimen korkeus: 4,18 cm





Features		Ports & interfaces	
Type *	Transmitter & receiver	PC Audio in	✓
Connectivity technology *	Wired	PC Audio out	✓
Cable types supported	Cat5e	Power	
Rack mounting	✓		- W
Maximum digital resolution	2560 x 2048 pixels	AC adapter output voltage	5 V
On Screen Display (OSD)	✓	Power consumption (transmitter) (max)	12.53 W
Product colour	Black	Power consumption (receiver) (max)	11.27 W
Material	Metal	Weight & dimensions	
LED indicators	✓	Transmitter width	21.5 cm
Certification	RoHS		16.3 cm
Transmitter		Transmitter depth	
Transmitter video port type	DVI-D	Transmitter height	4.18 cm
1 /1	DVI-D	Transmitter weight	1.17 kg
Transmitter local keyboard/mouse port type	USB	Receiver width	22.8 cm 17.2 cm
RJ-45 ports quantity (transmitter)	1	Receiver depth Receiver height	5.48 cm
Receiver		Receiver weight	1.28 kg
Receiver local video port type	DVI-D	Packaging content	
Receiver local keyboard/mouse port	USB	AC adapter included	✓
type RJ-45 ports quantity (receiver)	1	Cables included	KVM
		Manual	/
Ports & interfaces		On anational and ditions	
RS-232 ports	2	Operational conditions	
		Operating temperature (T-T)	0 - 50 °C
		Storage temperature (T-T)	-20 - 60 °C
		Operating relative humidity (H-H)	0 - 95%

