DELL H330 RAID-ohjain PCI Express x8 3.0 12 Gbit/s

Tuotemerkki : DELL **Tuotekoodi:** 405-AAFG

Tuotteen nimi : H330

DELL H330. Tuetut tallennusasemaliitännät: SAS, Serial ATA III, Isäntäkoneen käyttöliittymä: PCI Express x8. RAID-tasot: 0, 1, 5, 10, 50, Tiedonsiirtonopeus: 12 Gbit/s, Yhteensopivat tuotteet: PowerEdge FC630 PowerEdge M630P. Suoritinperhe: LSI, Prosessorimalli: SAS3008. Jännite: 12 V. Yhteensopivat käyttöjärjestelmät: Microsoft Windows Server 2008 R2 SP1 Microsoft Windows Server 2012 Microsoft Windows Server 2012...

Ports & interfaces

Supported storage drive interfaces *	SAS, Serial ATA III
Host interface *	PCI Express x8
PCI Express slots version	3.0
Internal mini-SAS ports	2

Performance

RAID levels *	0, 1, 5, 10, 50
RAID Level Migration	✔
Data transfer rate	12 Gbit/s
SSD support	✔
LED indicators	✔
S.M.A.R.T. support	✔
Number of devices supported	128
Online Capacity Expansion	✔
Compatible products	PowerEdge FC630 PowerEdge M630P

Processor

Built-in processor	✔
Processor family	LSI
Processor model	SAS3008

Power

Voltage	12 V

System requirements

Compatible operating systems	Microsoft Windows Server 2008 R2 SP1 Microsoft Windows Server 2012 Microsoft Windows Server 2012 R1 & R2 Red Hat Enterprise Linux 5.8 Red Hat Enterprise Linux 6.5 SUSE Linux Enterprise Server 10 SP4 SUSE Linux Enterprise Server 11 SP3 VMware ESXi 5.1 VMware 6.0

Operational conditions

Operating temperature (T-T)	0 - 65 °C
Storage temperature (T-T)	-45 - 105 °C
Operating relative humidity (H-H)	5 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions

Width	64.4 mm
Depth	167.6 mm

Logistics data

Harmonized System (HS) code	84733080

Other features

PCI Card form factor	Full-height (low-profile)
Hot-Plug support	✔

5397063981489

5711783357797