



## DELL 403-BBLZ interface cards/adapter Internal Fiber

Brand : DELL

Product code: 403-BBLZ

Product name : 403-BBLZ



Emulex LPe31000-M6-D Single Port 16Gb Fibre Channel HBA, Low Profile

DELL 403-BBLZ interface cards/adapter Internal Fiber:

- Support for Dell iDRAC8 with LifeCycle Controller and Emulex OneCommand manager to improve IT staff productivity through simplified deployment and management;
- T10 PI high-performance offload for advanced, end-to-end data integrity (requires support from SAN target solution).

Emulex LPe31000-M6-D Low Profile Single Port 16Gb Fibre Channel HBA with 16Gb FC connectivity (short wave optical – LC SFP+ included) from Dell™ are designed to address the demanding performance, reliability and management requirements of modern networked storage systems that utilize high performance and low latency solid state storage drives and HDD arrays. Compared to the previous generation, they provide up to 2x greater bandwidth, less than half the latency, and new features such as Forward Error Correction and enhanced diagnostics and I/O monitoring capabilities.

Ports & interfaces		System requirements	
Host interface *	PCIe	Windows operating systems supported	✓
Output interface *	Fiber	Linux operating systems supported	✓
Expansion card form factor	Low-profile	<b>Technical details</b>	
Expansion card standard	PCIe 3.0	Compliance certificates	RoHS
<b>Design</b>		<b>Packaging data</b>	
Internal *	✓	Quantity	1
Product colour	Green	<b>Logistics data</b>	
Purpose	Server	Harmonized System (HS) code	84733020
Certification	CSA, UL, FCC, RoHS, TUV Bauart, BSMI Class A, ICES Class A, VCCI Class A, MSIP Class A, RCM	<b>Other features</b>	
<b>Features</b>		Data transfer rate	14.025 Gbit/s
Data transfer rate (max)	14.025 Gbit/s	Ports quantity	1
<b>Operational conditions</b>		Data link protocols	16Gb Fibre Channel
Operating temperature (T-T)	0 - 55 °C	Connectivity technology	Wired
Operating relative humidity (H-H)	5 - 95%	Compatible operating systems	SUSE Linux Enterprise Server, Microsoft Windows, Red Hat Enterprise Linux
		Compatibility	PowerEdge C4130 PowerEdge FC630 PowerEdge FC830 PowerEdge R530 PowerEdge R630 PowerEdge R730 PowerEdge R730XD



5397063983711

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-FEB-2025. Prints or copies of Information are only valid on the printed Publication date