## FUĴÎTSU

## Fujitsu Intel Xeon Silver 4114 processor 2.2 GHz 13.75 MB L3

Brand : Fujitsu

Product code: S26361-F4051-E114

Product name : Intel Xeon Silver 4114

## Intel Xeon Silver 4114, 13.75M Cache, 2.2 GHz, 85 W TDP, FCLGA3647

Fujitsu Intel Xeon Silver 4114. Processor family: Intel Xeon Silver, Processor socket: LGA 3647 (Socket P), Processor lithography: 14 nm. Memory channels: Hexa-channel, Maximum internal memory supported by processor: 768 GB, Memory types supported by processor: DDR4-SDRAM. Market segment: Server, Supported instruction sets: AVX, AVX 2.0, AVX-512, SSE4.2, Scalability: 2S

Processor		Features	
FIGCESSUI			
Processor generation	1st Generation Intel® Xeon® Scalable	Maximum number of PCI Express lanes	48
Processor model *	4114	PCI Express slots version	3.0
Processor base frequency *	2.2 GHz	Supported instruction sets	AVX, AVX 2.0, AVX-512, SSE4.2
Processor family *	Intel Xeon Silver	Scalability	25
Processor cores *	10	Embedded options available	×
Processor socket *	LGA 3647 (Socket P)	Processor special features	
Component for	Server/workstation	Intel® Hyper Threading Technology	
Processor lithography *	14 nm	(Intel® HT Technology)	
Processor threads	20	Intel® Turbo Boost Technology	2.0
Processor operating modes * Processor boost frequency	64-bit 3 GHz	Intel® AES New Instructions (Intel® AES-NI)	<ul> <li>Image: A second s</li></ul>
Processor cache	13.75 MB	Enhanced Intel SpeedStep	1
Processor cache type	L3	Technology	
Thermal Design Power (TDP)	85 W	Intel Trusted Execution Technology	1
Stepping	LO	Intel <sup>®</sup> Speed Shift Technology	1
Processor codename	Skylake	Intel TSX-NI	1
Memory		Intel 64	1
Maximum internal memory supported by processor	768 GB	Intel Virtualization Technology (VT- x)	<ul> <li>Image: A start of the start of</li></ul>
Memory types supported by	DDR4-SDRAM	Conflict-Free processor	✓
processor Memory clock speeds supported by	2400 MHz	Intel Turbo Boost Max Technology 3.0	×
processor	Hexa-channel	Intel <sup>®</sup> Optane <sup>™</sup> Memory Ready	×
Memory channels * ECC		Intel® vPro <sup>™</sup> Platform Eligibility	✓
Graphics		Operational conditions	
•		Tcase	78 °C
On-board graphics card *	×		
Features			
Execute Disable Bit	1		
Market segment	Server		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.