Fujitsu PRIMERGY RX2510 M2 palvelin 0 GB Teline (1U) Intel® Xeon® E5 v4 E5-2623V4 2,6 GHz 16 GB DDR4-SDRAM 800 W

Tuotemerkki : Fujitsu

Tuoteperhe: PRIMERGY

Tuotekoodi: VFY:R2512SC200IN

Tuotteen nimi : RX2510 M2

Fujitsu PRIMERGY RX2510 M2. Suoritinperhe: Intel® Xeon® E5 v4, Prosessorin taajuus: 2,6 GHz, Prosessorimalli: E5-2623V4. Sisäinen muisti: 16 GB, Sisäisen muistin tyyppi: DDR4-SDRAM. Kokonaistallennuskapasiteetti: 0 GB. Ethernet LAN. Virtalähde: 800 W. Alustatyyppi: Teline (1U)

Processor manufacturer* Intell PCI Express slots version 3.0 Processor family* Intelle Keon® E5 v4 Design Processor frequency* 2.6 6Hz Rack (1U) Processor trequency 3.2 6Hz Performance Processor cache 10 MB Noise level 3.6 dB Memory channels supported by processor cache 0.0 MB Noise level 3.6 dB Number of processors installed 1 Software Microsoft Hyper-V Server 2016 Processor cache type Smatt Cache Software Microsoft Windows Server® 2016 Processor cache type Smatt Cache Software Microsoft Windows Server® 2016 Processor operating modes 64-bit Server ® 2016 Essentials Microsoft Windows Server® 2012 R2 Processor operating modes 64-bit Server ® 2016 Essentials Microsoft Windows Server® 2012 R2 Stepping Ro Server ® 2016 Essentials Server ® 2012 R2 Standard Microsoft Windows Server 2012 R2 Standard Microsoft Windows Server 2012 R2 Standard Microsoft Windows Server 2012 R2 Standard Microsoft Windows Server 2012 R2 Standard Microsoft Windows Server 2012 R2 Standard Microsoft Windows Server 2012 R2 Standard Microsoft Windows Server 2012 R2 Standard Microsoft Windows Server 2012 R2	Processor		Expansion slots	
Processor familyIntel® Xeon® E5 v4 E5-8623V4DesignProcessor frequency2.6 GHzRack mountingAck (1U)Processor boost frequency3.2 GHzRack mountingAProcessor cache10 MBNoise level36 dBMemory channels supported by processor cacheQuadBIOS typeUFINumber of processors installed1SoftwareMicrosoft Hindrow Server 2016 Microsoft Windrow Server 2016 		latal.	•	2.0
Processor frequencyES-2623V4ProductionProcessor frequency2.6 GHzRack mountingRack (LU)Processor formance3.2 GHzRack mountingProcessor carbos0.0 MBNoise level3.6 dBMemory channels supported by processorQuadBIOS type (Decessor Sector)UEFINumber of processor sinstalled1SoftwareUEFIProcessor carbos6 GT/SMicrosoft Windows Server® 2016 EssentialsNicrosoft Windows Server® 2016 EssentialsProcessor carbos6 GT/SServer® 2016 EssentialsNicrosoft Windows Server® 2016 EssentialsProcessor socketLGA 2011-v3Nicrosoft Windows Server® 2016 EssentialsProcessor operating modes6-bitServer® 2016 EssentialsProcessor operating modes6-bitNicrosoft Windows Server® 2012 R2 DatacenterProcessor operating modes14 nmSoftwaresProcessor operating modes6-bitNicrosoft Windows Server® 2012 R2 DatacenterNumber of QPI links2Nicrosoft Windows ServerProcessor operating modes154 TBNicrosoft Windows ServerNumber of QPI links0Nicrosoft Windows ServerProcessor pocksor6-3 GB/SNicrosoft Windows ServerNumber of QPI links0Nicrosoft Windows ServerProcessor pocksor6-3 GB/SNicrosoft Windows ServerSupported by processor6-3 GB/SNicrosoft Windows ServerProcessor package size4-3 SLS AmaNicrosoft Windows ServerUBIA Standard Microsoft Windows <td></td> <td></td> <td>PCI Express slots version</td> <td>3.0</td>			PCI Express slots version	3.0
Processor frequency* 2.6 GHz Chassis type* Rack mounting Rack mounting Processor cose 4 Performance 3.6 dB Processor cache 10 MB Noise level 3.6 dB Memory channels supported by processor cache 1 Software Microsoft Hyper-V Server 20.16 Microsoft Windows Server? Thermal Design Power (TDP) 58 W Microsoft Windows Server? Software Processor cache type Snatt Cache Software Microsoft Windows System bus rate 8 GTs Software Microsoft Windows Processor poscket LGA 2011-v3 Windows Sortware Processor operating modes 6-bit Software Server 20.12 R2 Datacenter Microsoft Windows Processor operating modes 6-bit Server 20.12 R2 Datacenter Microsoft Windows Server 20.12 R2 Stepping Ro Standard Microsoft Windows Server 20.12 R2 Stepping Ro Standard Microsoft Windows Server 20.12 R2 Standard Microsoft Windows Server 20.12 R2 Datacenter Microsoft Windows Server 20.12 R2 Standard Microsoft Windows Server 20.12 R2 Tase 73 °C Standard Microsoft Windows Server 20.12 R2 Tase 154 TB Microsoft Windows Server 20.12 R2 Memory types supported by procesor F Standard Microsoft Windows Server 2	•		Design	
Processor cores3.2 GHzRack mounting*Processor cores4Performance*Processor cores10 MBNoise level36 dBMemory channels supported by processorQuadBIOS typeUEFINumber of processors installed1Software*Thermal Design Power (TDP)85 WSoftwareMicrosoft Mindows Sorver® 2016Processor socketLGA 2011-v3*Microsoft Mindows Sorver® 2016Processor socketLGA 2011-v3Windows Sorver® 2016Sindard Microsoft Mindows Sorver® 2016Processor threads8Server® 2016 Sindard Microsoft Mindows Sorver® 2012 R2 DatacenterSindard Microsoft Mindows Server 2012 R2 DatacenterProcessor codenameBroadwell2Sindard Microsoft Mindows Server 2012 R2 DatacenterWindows Server 2012 R2 DatacenterNumber of OPI links2Sindard Microsoft Mindows Server 2012 R2 Datacenter*Windows Server 2012 R2 DatacenterNaximum internal memory supported by processorDDR4-SDRAMServer 2012 R2 Datacenter**Memory bandwidth supported by processorSindard Microsoft Mindows Server 2012 R2 Datacenter**Memory bandwidth supported by processorSindard Microsoft Windows Server 2012 R2 Datacenter**Memory bandwidth supported by processorSindard Microsoft Windows Server 2012 R2 Datacenter**Microsoft Windows Server 2013 R2 Microsoft WindowsServer 2012 R2 Datacenter**Microsoft Windows Server 2013 R2 Microsoft Windows**			Chassis type *	Rack (1U)
Processor cache4PerformanceProcessor cache10 MBNoise level36 dBMemory channels supported by processorsQuadBIOS typeUEFINumber of processors installed1SoftwareMicrosoft Hyper-V Server 2016Processor cache typeSmat CacheSoftwareMicrosoft Hyper-V Server 2015System bus rate8 GT/SMicrosoft Hyper-V Server 2016Sistem CacheProcessor socketLGA 2011-v3Microsoft Mindows Server P 2016Sistem CacheProcessor operating modes64-bitMicrosoft MindowsServer 2012 R2 Microsoft WindowsProcessor operating modes64-bitSistem CacheSistem CacheSupported bypOPISupported NindowsServer 2012 R2 Microsoft WindowsNumber of QPI links2Standard Microsoft WindowsServer 2012 R2 Microsoft WindowsSupported byp processorPOR4-SDRAMServer 2012 R2 Microsoft WindowsServer 2012 R2 Microsoft WindowsMemory types supported by processorDR4-SDRAMServer 2012 R2 Microsoft WindowsServer 2012 R2 Microsoft WindowsMemory types supported by processorServer 2012 R2 Microsoft WindowsServer 2012 R2 Microsoft WindowsMemory types supported by processorServer 2013 R2 Microsoft WindowsServer 2012 R2 Microsoft WindowsMemory types supported by processorServer 2014 R2 Microsoft WindowsServer 2012 R2 Microsoft WindowsMemory types supported by processorServer 2015 R2 Microsoft WindowsServer 2012 R2 Microsoft WindowsMemory types supporte			Rack mounting	1
Processor cache processor processor stalled10 MBNoise level36 dBMemory channels supported by processor stalled1SoftwareUEFINumber of processors installed1SoftwareMicrosoft Hyper V Server 2016 Datacenter Microsoft Windows Server® 2016 Standard Microsoft Windows Server® 2018 Server 2012 R2 Datacenter Windows Server® 2018 R2 Microsoft Windows Server® 2018 R2 Microsoft Windows Server® 2018 R2 Microsoft Windows Server® 2012 R2 Datacenter Windows Server® 2012 Microsoft Windows Server 2012 Datacenter Microsoft Windows Server 2012 Datacenter Microsoft Windows Server 2012 Standard Microsoft Windows Server <td></td> <td></td> <td>Performance</td> <td></td>			Performance	
Memory channels supported by processorQuadBIOS TypeUFFINumber of processors installed1SoftwareUFFIThermal Design Power (TDP)85 WMicrosoft Hyper-V Server 2016 Microsoft WindowsServer® 2016 Standard Microsoft Windows Server® 2016 Standard Microsoft Windows 				26 49
SoftwareSoftwareNumber of processor sinstalled1Microsoft Hyper-V Server 2016Thermal Design Power (TDP)85 WMicrosoft Windows Server 9: 2016Processor socket66 X 2011-v3Server 9: 2016 Estandard Microsoft WindowsProcessor Inforpaphy14 nmMicrosoft Windows Server 9: 2016 Estandard Microsoft Windows Server 2012 R2 Discosoft Windows Server 2012 Discosoft Windows Server 2012 Discosoft Windows Server 2012 Discosoft Windows Server 2012 R2 Standard Microsoft Windows Server 2012 Discosoft Windows Server 2012 R2 Standard Microsoft Win	Memory channels supported by			
Processor cache typeSmart CacheMicrosoft WindowsServer® 2016System bus rate8 GT/sServer® 2016Standard MicrosoftProcessor socketLGA 2011-v3WindowsServer® 2016Processor tihography14 nm2016Standard MicrosoftProcessor tihography64-bitServer 2012 R2 DatacenterMicrosoft WindowsSteppingR0Server 2012 R2 DatacenterServer 2012 R2 DatacenterBus typeQPI2016Standard MicrosoftWindowsProcessor codenameBroadwellZurcosoft WindowsServer 2012 R2Tcase73 °CVindowsServer 2012 R2 Sentials MicrosoftProcessor codename73 °CZollz Datacenter Microsoft WindowsServer 2012 R2Tcase73 °CZollz Datacenter Microsoft WindowsServer 2012 R2Memory types supported by processorDR4-SDRAMServer 2012 R2Sentials Microsoft WindowsMemory types supported by processorBio.1866,2133 MHzServer 2008 R2 Microsoft WindowsServer 2008 R2 Microsoft WindowsMemory types supported by processor68.3 GB/sServer 2008 R2 Standard Microsoft WindowsServer 2008 R2 Standard Microsoft WindowsServer 208 R2 Microsoft WindowsServer 2012 R2Server 2012 R2Server 2012 R2Memory types supported by processor68.3 GB/sServer 2008 R2 Standard Microsoft WindowsServer 2012 R2Memory types supported by processorCServer 2008 R2 Standard Microsoft WindowsServer 2008 R2 Standard Microsoft WindowsServer	Number of processors installed	1	Software	
Processor Cache UpeShart CacheDatacenter Microsoft WindowsSystem bus rate8 GT/SServer8 2016 EssentialsProcessor socketLGA 2011-v3WindowsProcessor socketLGA 2011-v3WindowsProcessor threads8Server8 2016 EssentialsProcessor threads64-bitServer 2012 R2 Microsoft WindowsSteppingR0Server 2012 R2 Microsoft WindowsSteppingR0Server 2012 R2 DatacenterMicrosoft Pyper VProcessor codenameBroadwellTcase73 °CWindows Server 2012 R2 Server 2008 R2 Server 2	Thermal Design Power (TDP)	85 W		Microsoft Windows Server® 2016 Datacenter Microsoft Windows Server® 2016 Standard Microsoft Windows Server® 2016 Essentials Microsoft Windows Storage Server 2016 Standard Microsoft Hyper-V Server 2012 R2 Microsoft Windows Server 2012 R2 Datacenter Microsoft Windows Server 2012 R2 Standard Microsoft Windows Server
System bus rate8 GT/sServer® 2016 Standard Microsoft Windows Server® 2016 Standard Microsoft Windows Storage Server Server 2012 R2 Microsoft Windows Server 2012 R2 Microsoft Windows Server 2012 R2 Datacenter Windows Server 2012 R2 Microsoft Windows Server 2012 R2 Datacenter Windows Server 2012 R2 Datacenter Windows Server 2012 R2 Datacenter 	Processor cache type	Smart Cache		
Processor socketIGA 2011-v3Kindows Server 2012 R2sentials Microsoft Windows Storage Server 2016 Standard Microsoft Hyper-V Server 2012 R2 Datacenter 	System bus rate	8 GT/s		
Processor Integraphy14 Intri2016 Standard Microsoft Hyper-VProcessor Integraphy8Server 2012 R2 Microsoft WindowsProcessor IntegraphyR0Server 2012 R2 Costandard Microsoft WindowsSteppingR0Standard Microsoft WindowsBus typeQPIStandard Microsoft WindowsNumber of QPI links2Standard Microsoft WindowsProcessor IntegraphyBroadwellStandard Microsoft WindowsTcase73 °CStandard Microsoft MindowsWaximum internal memory1.54 TBServer 2012 R2Memory types supported by processorDDR4-SDRAMServer 2012 Standard Microsoft WindowsProcessor (max)1.60,1866,2133 MHzServer 2008 R2 Datacenter Microsoft WindowsMemory bandwidth supported by processorR00,1866,2133 MHzServer 2008 R2 Datacenter Microsoft WindowsMemory bandwidth supported by processorServer 2008 R2 Datacenter Microsoft WindowsCS supported by processorServer 2008 R2 Datacenter Microsoft WindowsCS supported by processorServer 2008 R2 Datacenter Microsoft WindowsCS supported by processor (max)Idle StatesServer 2012 R2Standard Microsoft WindowsServer 2013 R2Server 2008 R2 Ustandard Microsoft WindowsServer 2014 R2Server 2015 R2Processor (max)Kerver VD R2Server 2013 R2Server	Processor socket	LGA 2011-v3		
Processor threads8Server 2012 R2 Microsoft WindowsProcessor operating modes64-bitServer 2012 R2 Microsoft Windows Server 2012 R2Standard Microsoft Windows Server 2012 R2Standard Microsoft Windows Server 2012 R2Bus typeOPI"Windows Storage Server 2012 R2Processor codenameBroadwell"Standard Microsoft Windows Server 2012 R2Tcase73 °C"Zotacenter Microsoft Windows Server 2012 R2Maximum internal memory1.54 TB"Zotacenter Microsoft Windows Server 2012 R2Memory types supported by processorDR4-SDRAM"Server 2012 R2 Essentials Microsoft Windows Server 2012 R2Memory types supported by processor1600,1866,2133 MHzServer 2012 R2 Essentials Microsoft Windows Server 2008 R2 Micro	Processor lithography	14 nm		
Stepping SteppingNumbersMicrosoftMicr	Processor threads	8		
SuppringRoStandard Microsoft Windows Server 2012 R2 Essentials Microsoft Windows Storage Server 2012 R2 Standard Microsoft Hyper-V Server 2012 Datacenter Microsoft Windows Server 2008 R2 Microsoft Windows Server 2008 R2 Microsoft Windows Server 2012 Datacenter Microsoft Windows Server 2008 R2 Microsoft Windows Server 20	Processor operating modes	64-bit		
Bus typeQPI2012 A2 Essentials MicrosoftNumber of QPI links2Vindows Storage Server 2012 A2Processor codenameBroadwell2012 Datacenter Microsoft Windows Storage Server 2012 Standard Microsoft Windows Server 2018 Z Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter 2012 Standard Microsoft Windows Server 2008 R2 Datacenter 2015 Standard Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter 2015 Standard Microsoft Windows Server 2008 R2 Datacenter 2015 Standard Microsoft Windows Server 2008 R2 Standard Windows Server 2008 R2 Standard Microsoft Windows Server 2008 R2 Standard Microsoft Windows Server 2008 R2 Standard Windows Server 2012 Microsoft Windows Server 2012 Mi	Stepping	RO		
Number of processorBroadwellStandard Microsoft Hyper-V Server 2012 Microsoft Windows Server 2012 Microsoft Windows Server 2012 Datacenter Microsoft Windows Server 2012 Datacenter Microsoft Windows Server 2012 Datacenter Microsoft Windows Server 2012 Standard Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Storage Server 2012 Standard Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter windows Server 2008 R2 Datacenter windows Server 2008 R2 Datacenter wicrosoft Windows Server 2008 R2 Datacenter wicrosoft Windows Server 2008 R2 Datacenter <br< td=""><td>Bus type</td><td>QPI</td><td rowspan="3"></td></br<>	Bus type	QPI		
Processor codenameBroadwell2012 Microsoft Windows ServerTcase73 °C2012 Datacenter Microsoft WindowsMaximum internal memory supported by processor1.54 TB2012 Datacenter Microsoft WindowsMemory types supported by processorDDR4-SDRAMServer 2012 Standard Microsoft WindowsMemory clock speeds supported by processor68.3 GB/sServer 2008 R2 Datacenter Microsoft WindowsMemory bandwidth supported by processor (max)68.3 GB/sServer 2008 R2 Datacenter Microsoft WindowsEcc supported by processorViname vSphere 6.0 VindowsKerust Disable BitIde StatesMaximum number of PCI Express lanes40Supported instruction setsAVX 2.0Enhanced Intel SpeedStep TechnologySupported instruction setsAVX 2.0Enhanced Intel SpeedStep Technology (Intel® IPT)Scalability25Intel ® Intel ® Intel Winter ProcessorPhysical Address Extension (PAE)Intel ® Intel ® Intel ® IPT)Physical Address Extension (PAE)Intel ® Hatel ® IPT)Physical Address Extension (PAE)Intel ® Hatel ® IPT)Processor seriesIntel Xen E5-2600 v4Intel ® Threading TechnologyConflict-Free processorIntel ® Threading TechnologyConflict-Free processorIntel ® Threading TechnologyScalability25Intel ® Hatel © IPT)	Number of QPI links	2		
Tcase73 °C2012 Datacenter Microsoft Windows Server 2012 Standard Microsoft Windows Server 2012 Essentials Microsoft Windows Server 2012 Essentials Microsoft Windows Server 2012 Essentials Microsoft Windows Server 2012 Essentials Microsoft Windows Server 2008 R2 Server 2008 R2 Datacenter Processor2012 Datacenter Microsoft Windows Server 2012 Essentials Microsoft Windows Server 2008 R2 Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Server 2008 R2 Datacenter Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Server 2008 R2 Da	Processor codename	Broadwell		2012 Microsoft Windows Server 2012 Datacenter Microsoft Windows Server 2012 Standard Microsoft Windows Server 2012 Essentials Microsoft Windows Storage Server 2012 Standard Microsoft Hyper-V Server 2008 R2 Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Enterprise Microsoft Windows Server 2008 R2 Standard VMware vSphere 6.5 VMware vSphere 6.0 VMware vSphere 5.5 SUSE Linux Enterprise Server 12 SUSE Linux Enterprise Server 11 Red Hat Enterprise Linux 7 Red Hat Enterprise Linux 6 Oracle Linux 7
Maximum internal memory supported by processor1.54 TBWindows Server 2012 Standard Microsoft Windows Server 2012 Standard Microsoft Windows Server 2012 Standard Microsoft Windows Server 2012 Standard Microsoft Hyper-V Server 2018 R2 Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Standard VMware Server 2008 R2 Standard VMware Server 2008 R2 Standard VMware Sphere 6.0 VMware VSphere 6.5 SUSE Linux Enterprise Microsoft Windows Server 2008 R2 Standard VMware Sphere 6.0 VMware VSphere 6.0 VMware VSphere 6.5 SUSE Linux Enterprise Server 12 SUSE Linux Enterprise Server 12 SUSE Linux Enterprise Linux 7 Red Hat Enterprise Linux 7 Red Hat 	Tcase	73 °C	Compatible operating systems *	
Memory types supported by processorDDR4-SDRAM2012 Standard Microsoft Hyper-V Server 2008 R2 Microsoft Windows Server 2008 R2 Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Standard MWare Server 20	Maximum internal memory supported by processor	1.54 TB	compatible operating systems *	
Memory clock speeds supported by processor (max)1600,1866,2133 MHzServer 2008 R2 Datacenter Microsoft Windows Server 2008 R2 Enterprise Microsoft Windows 	Memory types supported by processor	DDR4-SDRAM		
norocessor (max)Server 2008 R2 Standard VMware vSphere 6.5 VMware vSphere 6.0 VMware vSphere 6.5 VMware vSphere 6.0 VMware vSphere 6.5 VMware vSphere 6.0 	Memory clock speeds supported by processor	1600,1866,2133 MHz		
ECC supported by processorExecute Disable BitEnterprise Server 12 SUSE Linux Enterprise Server 11 Red Hat Enterprise Server 11 Red Hat Enterprise Linux 7 Red Hat Enterprise Linux 7 Red Hat Enterprise Linux 6 Oracle Linux 7 Oracle VM 3Maximum number of PCI Express lanes40Processor package size45 x 52.5 mmCPU configuration (max)2Supported instruction setsAVX 2.0Enhanced Intel SpeedStep TechnologySolability25Intel ® Identity Protection Directed I/O (VT-d)Physical Address Extension (PAE)Intel Server 11 Red Hat Enterprise Linux 7 Red Hat Enterprise Linux 7 Red Hat Enterprise Linux 7 Oracle Linux 7 Oracle VM 3Physical Address Extension (PAE)Physical Address Extension (PAE)Processor seriesIntel Xeon E5-2600 v4Intel Wirtualization TechnologyProcessor seriesIntel Xeon E5-2600 v4Intel ® Turbo Boost TechnologyConflict-Free processorIntel ® Turbo Boost Technology	Memory bandwidth supported by processor (max)	68.3 GB/s		
Execute Disable BitEnterprise Server 12 SUSE Linux Enterprise Server 11 Red Hat Enterprise Linux 7 Red H	ECC supported by processor	✓		
Idle StatesInterprise Linux 7 Red Hat Enterprise Linux 6 Oracle Linux 7 Oracle VM 3Thermal Monitoring TechnologiesImage: Construction Sets40Maximum number of PCI Express lanes40Processor special featuresProcessor package size45 x 52.5 mmCPU configuration (max)2Supported instruction setsAVX 2.0Enhanced Intel SpeedStep TechnologyImage: Construction (max)2Scalability25Intel® Identity Protection Technology (Intel® IPT)Image: Construction SetsImage: Construction SetsPhysical Address Extension (PAE)46 bitIntel Virtualization Technology for Directed I/O (VT-d)Image: Construction SetsImage: Construction SetsPhysical Address Extension (PAE)XImage: Construction SetsImage: Construction SetsImage: Construction SetsPhysical Address Extension (PAE)KImage: Construction SetsImage: Construction SetsImage: Construction SetsPhysical Address Extension (PAE)KImage: Construction SetsImage: Construction SetsImage: Construction SetsPhysical Address Extension (PAE)KImage: Construction SetsImage: Construction SetsImage: Construction SetsPhysical Address Extension (PAE)KImage: Construction SetsImage: Construction SetsImage: Construction SetsProcessor seriesImage: Construction SetsKImage: Construction SetsImage: Construction SetsImage: Construction SetsConflict-Free processorImage: Construction SetsImage: Construction SetsImage: Construction Sets	Execute Disable Bit	 Image: A second s		
Thermal Monitoring TechnologiesImage: Section of PCI Express Avainang number of PCI Express hanesImage: Section of PCI Express h	Idle States	Image: A start of the start		
Maximum number of PCI Express lanes40Processor special featuresProcessor package size45 x 52.5 mmCPU configuration (max)2Supported instruction setsAVX 2.0Enhanced Intel SpeedStep TechnologyProcessor codeSR2PJIntel® Identity Protection Technology (Intel® IPT)Scalability2SIntel® Identity Protection Directed I/O (VT-d)Physical Address Extension (PAE)46 bitIntel Virtualization Technology for Directed I/O (VT-d)Processor seriesIntel Xeon E5-2600 v4Intel® Hyper Threading Technology (Intel® HT Technology)Conflict-Free processor<	Thermal Monitoring Technologies	1		
Supported instruction setsAVX 2.0Enhanced Intel SpeedStep TechnologyProcessor codeSR2PJTechnologyScalability2SIntel® Identity Protection Technology (Intel® IPT)×Physical Address Extension (PAE)Intel Virtualization Technology for Directed I/O (VT-d)Embedded options available×Intel® Hyper Threading TechnologyProcessor seriesIntel Xeon E5-2600 v4Intel® Turbo Boost Technology2.0	Maximum number of PCI Express lanes	40	Processor special features	
Supported instruction setsAVX 2.0Enhanced Intel SpeedStep TechnologyProcessor codeSR2PJTechnologyScalability2SIntel® Identity Protection Technology (Intel® IPT)Physical Address Extension (PAE)46 bitIntel Virtualization Technology for Directed I/O (VT-d)Embedded options availableXIntel® Hyper Threading TechnologyProcessor seriesIntel Xeon E5-2600 v4Intel® Turbo Boost Technology2.0	Processor package size	45 x 52.5 mm	•	2
Processor codeSR2PJTechnologyScalability2SIntel® Identity Protection Technology (Intel® IPT)Physical Address Extension (PAE)<	Supported instruction sets	AVX 2.0		-
Physical Address Extension (PAE) Technology (Intel® IPT) Physical Address Extension (PAE) 46 bit Intel Virtualization Technology for Directed I/O (VT-d) Embedded options available × Intel® Hyper Threading Technology Processor series Intel Xeon E5-2600 v4 Intel® Turbo Boost Technology 2.0	Processor code	SR2PJ	· · ·	1
Physical Address Extension (PAE) Intel Virtualization Technology (Intel® IPT) Physical Address Extension (PAE) 46 bit Intel Virtualization Technology for Directed I/O (VT-d) Embedded options available Yerocessor series Intel Xeon E5-2600 v4 Intel® Hyper Threading Technology Vortel® HT Technology 2.0	Scalability	25		*
Provisical Address Extension (PAE) 46 bit Directed I/O (VT-d) Embedded options available × Intel® Hyper Threading Technology Processor series Intel Xeon E5-2600 v4 (Intel® HT Technology) Conflict-Free processor ✓ Intel® Turbo Boost Technology	Physical Address Extension (PAE)	✓		0
Processor series Intel Xeon E5-2600 v4 (Intel® HT Technology) Conflict-Free processor ✓ Intel® Turbo Boost Technology 2.0	Physical Address Extension (PAE)			1
Conflict-Free processor	Embedded options available Processor series			1
			557	2.0
	connective processor	-	5,	

Memory		Processor special features	
Internal memory * Internal memory type *	16 GB DDR4-SDRAM	Intel® AES New Instructions (Intel® AES-NI)	1
Memory slots	12	Intel Trusted Execution Technology	1
Memory clock speed	2400 MHz	Intel Enhanced Halt State	✓
Maximum internal memory *	384 GB	Intel VT-x with Extended Page	1
Storage		Tables (EPT) Intel Demand Based Switching	,
Total storage capacity *	0 GB	5	
RAID support *	1	Intel® Secure Key	
RAID levels	0, 1, 5, 6, 10, 50, 60	Intel TSX-NI	
Supported RAID controllers	Fujitsu PRAID EP420i, Fujitsu PRAID	Intel® OS Guard	✓
	EP400i, Fujitsu PRAID CP400i	Intel 64	✓
Optical drive type *	×	Intel Identity Protection Technology version	0.00
Network		Intel Secure Key Technology version	1.00
Ethernet LAN	1	Intel Virtualization Technology (VT-	1
Ports & interfaces		x) Intel TSX-NI version	1.00
Ethernet LAN (RJ-45) ports *	2	Processor ARK ID	92980
USB 2.0 ports quantity	2		52500
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	4	Power	000.11/
ports quantity VGA (D-Sub) ports quantity	1	Power supply *	800 W
Serial ports quantity	1	Number of redundant power supplies supported	1
Expansion slots	-	Number of main power supplies	1
•	2	Operational conditions	
PCI Express x8 (Gen 3.x) slots	2	Operating temperature (T-T)	5 - 45 °C
PCI Express x16 (Gen 3.x) slots	2	Operating relative humidity (H-H)	10 - 85%
		Weight & dimensions	
		Width	483 mm

Depth Height

Weight

Technical details Number of 2.5" bays

Number of 3.5" bays

770 mm

43 mm

16 kg

8

4

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.