



## Lindy 300m Cat.6 2 Port VGA Receiver

**Brand :** Lindy

**Product code:** 35404

**Product name :** 300m Cat.6 2 Port VGA Receiver

- Receives VGA signals over 300m network cable from the compatible transmitter (35403)
- Distribute the received signal across 2 separate VGA displays
- Supports resolutions up to 1920x1080, with dual mono audio extraction
- Adjustable EQ and gain control for ensuring optimum image quality
- 2 year warranty

300m Cat.6 2 Port VGA Receiver

Lindy 300m Cat.6 2 Port VGA Receiver. Video port type: VGA, Video out: VGA. Maximum resolution: 1920 x 1080 pixels, Product colour: Black, HD type: Full HD. Cable types supported: Cat5e, Cat6. AC input voltage: 12 V, Input current: 1.2 A. Width: 135.4 mm, Depth: 73 mm, Height: 31 mm



| Ports & interfaces             |                    | Weight & dimensions               |             |
|--------------------------------|--------------------|-----------------------------------|-------------|
| Video port type *              | VGA                | Depth                             | 73 mm       |
| Video out *                    | VGA                | Height                            | 31 mm       |
| Ethernet LAN (RJ-45) ports     | 4                  | Weight                            | 484 g       |
| Video ports quantity *         | 1                  | <b>Packaging data</b>             |             |
| Audio ports quantity           | 1                  | Package width                     | 177 mm      |
| DC-in jack                     | ✓                  | Package depth                     | 110 mm      |
| <b>Features</b>                |                    | Package height                    | 75 mm       |
| Product colour                 | Black              | Package weight                    | 547 g       |
| Maximum resolution *           | 1920 x 1080 pixels | <b>Packaging content</b>          |             |
| HD type                        | Full HD            | Manual                            | ✓           |
| Maximum operating distance     | 300 m              | AC adapter included               | ✓           |
| LED indicators                 | ✓                  | <b>Operational conditions</b>     |             |
| <b>Network</b>                 |                    | Operating temperature (T-T)       | 0 - 50 °C   |
| Cable types supported          | Cat5e, Cat6        | Storage temperature (T-T)         | -20 - 70 °C |
| <b>Power</b>                   |                    | Operating relative humidity (H-H) | 20 - 80%    |
| AC input voltage               | 12 V               | <b>Technical details</b>          |             |
| Input current                  | 1.2 A              | Compliance certificates           | REACH, RoHS |
| <b>Weight &amp; dimensions</b> |                    | <b>Logistics data</b>             |             |
| Width                          | 135.4 mm           | Harmonized System (HS) code       | 85176990    |



4002888354042

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 27-FEB-2025. Prints or copies of Information are only valid on the printed Publication date