

iiyama ProLite T1634MC-B1S tietokoneen litteä näyttö 39,6 cm (15.6") 1920 x 1080 pikseliä Full HD LED Kosketusnäyttö musta

Tuotemerkki : iiyama

Tuoteperhe: ProLite

Tuotekoodi: T1634MC-B1S

Tuotteen nimi : T1634MC-B1S

iiyama ProLite T1634MC-B1S. Näytön halkaisija: 39,6 cm (15.6"), Näytön erottelutarkkuus: 1920 x 1080 pikseliä, HD-tyyppi: Full HD, Näytön teknologia: LED, Näytön pinta: Matta, Vakiokuvasuhde: 16:9, Katselukulma, vaakasuora: 178°, Katselukulma, pystysuora: 178°. VESA-kiinnitys. Tuotteen väri: musta



Display		Ergonomics	
Display diagonal *	39.6 cm (15.6")	VESA mounting *	✓
Display resolution *	1920 x 1080 pixels	Panel mounting interface	100 x 100 mm
HD type *	Full HD	Tilt adjustment	✓
Native aspect ratio *	16:9	Tilt angle range	90 - 5°
Display technology *	LED	On Screen Display (OSD)	✓
Panel type *	IPS		
Touchscreen *	✓	Power	
Touchscreen technology	Projected capacitive system	Energy efficiency class (SDR) *	E
Number of simultaneous touchpoints	10	Energy efficiency class (HDR) *	Not available
Display brightness (peak)	450 cd/m ²	Energy consumption (SDR) per 1000 hours *	10 kWh
Display brightness (typical)	405 cd/m ²	Power consumption (typical) *	18 W
Display surface	Matt	Power consumption (standby) *	1.5 W
Screen shape *	Flat	Power consumption (off)	0.3 W
Contrast ratio (typical) *	700:1	Power supply type	External
Maximum refresh rate *	60 Hz	Energy efficiency scale	A to G
Viewing angle, horizontal	178°	European Product Registry for Energy Labelling (EPREL) code	1530736
Viewing angle, vertical	178°	Weight & dimensions	
Display number of colours *	16.2 million colours	Width (with stand)	381 mm
Response time (fast)	25 ms	Depth (with stand)	200 mm
Pixel pitch	0.179 x 0.179 mm	Height (with stand)	285.5 mm
Digital horizontal frequency	30 - 84 kHz	Weight (with stand)	3.4 kg
Display diagonal (metric)	39.5 cm	Packaging data	
Colour depth	6 bit	Package width	445 mm
Colour gamut	90%	Package depth	150 mm
Design		Package height	355 mm
Market positioning *	Office	Package weight	5.18 kg
Product colour *	Black	Packaging content	
Glass thickness	2.4 mm	Cables included	AC, DisplayPort, HDMI, USB
Ports & interfaces		Other features	
VGA (D-Sub) ports quantity	1	International Protection (IP) code	IP65
HDMI *	✓	Second display effective viewing area	344.2 x 193.6 mm
HDMI ports quantity	1		
DisplayPorts quantity	1		
HDCP	✓		



4948570122110

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-MAR-2025. Prints or copies of Information are only valid on the printed Publication date