

Lindy 4 Port USB 3.0 Hub with On/Off Switches

Brand : Lindy Product code: 43309

Product name: 4 Port USB 3.0 Hub with On/Off Switches

- Allows 4 USB 3.0 devices to be connected to a single port
- On/Off switch on each port allows users to manage power consumption of the connected devices
- SuperSpeed transfer rates up to 5Gbps, backwards compatible with USB 2.0 / 1.1
- Bus-powered with optional USB Micro-B socket for use with high powered devices
- 2 year warranty
- 4 Port USB 3.0 Hub with On/Off Switches

Lindy 4 Port USB 3.0 Hub with On/Off Switches:

A USB hub connects to a PC or laptop and provides additional USB ports for connecting multiple peripherals or other devices simultaneously.

The Lindy 4 Port USB 3.0 Hub provides convenient access and effective power management for USB peripherals and storage devices. Capable of data transfer speeds of up to 5Gbps, the hub is also backwards compatible with USB 2.0 and 1.1.

The hubs individual On/Off switching ports can help reduce overall power consumption and are perfect for accessing external hard drives or other periodically used devices. An optional power supply can be connected for use with high current USB devices.





	Weight & dimensions	
Host interface * USB 3.2 Gen 1 (3.1 Gen 1) Type-A Hub interfaces * USB 3.2 Gen 1 (3.1 Gen 1) Type-A USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Weight	42 g
	Packaging data	
4	Package width	174 mm
4	Package depth	194 mm
	Package height	15 mm
E 141 % /	Package weight	60 g
Product colour Grey	Packaging content	
	Cables included	USB Type-A to USB Type-B
(ABS), Aluminium, Polycarbonate	Manual	✓
(PC)	Operational conditions	
	Operating temperature (T-T)	0 - 50 °C
USB	, , , , , ,	32 - 122 °F
5 V	Storage temperature (T-T)	0 - 60 °C
	Operating relative humidity (H-H)	0 - 85%
100 mm	Logistics data	
30 mm	Harmonized System (HS) code	84719000
	USB 3.2 Gen 1 (3.1 Gen 1) Type-A 4 4 5 Mbit/s Grey Acrylonitrile butadiene styrene (ABS), Aluminium, Polycarbonate (PC) USB 5 V	USB 3.2 Gen 1 (3.1 Gen 1) Type-A USB 3.2 Gen 1 (3.1 Gen 1) Type-A Packaging data Package width Package depth Package height Package weight Manual Packaging content Cables included Manual Operational conditions Operating temperature (T-T) Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Logistics data Harmonized System (HS) code



4002888433099

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.