Philips E-Line 65BDL3152E Digitaalinen litteä infotaulu 165,1 cm (65") 350 cd/m² 4K Ultra HD musta Kosketusnäyttö Sisäänrakennettu prosessori Android 16/7



Tuotemerkki : Philips

Tuotekoodi: 65BDL3152E/00

Tuotteen nimi : E-Line 65BDL3152E

Philips E-Line 65BDL3152E. Tuotteen muotoilu: Digitaalinen litteä infotaulu. Näytön halkaisija: 165,1 cm (65"), Näytön erottelutarkkuus: 3840 x 2160 pikseliä, Näytön kirkkaus: 350 cd/m², HD-tyyppi: 4K Ultra HD, Kosketusnäyttö. Toiminta-aika (tunteja/päiviä): 16/7. Käyttöjärjestelmä asennettu: Android. Tuotteen väri: musta

| Display | | Performance | |
|--|--|---|---|
| Panel type | ADS | Purpose * | Universal |
| Display diagonal * | 165.1 cm (65") | On Screen Display (OSD) | 1 |
| Display resolution * | 3840 x 2160 pixels | · - | Arabic, Simplified Chinese, |
| Display brightness * | 350 cd/m ² | | Traditional Chinese, Danish, |
| HD type * | 4K Ultra HD | On Screen Display (OSD) languages | German, Dutch, English, Spanish, Finnish, French, Italian, Japanese, |
| Touchscreen * | ✓ | | Norwegian, Polish, Portuguese, |
| Touchscreen technology | Infrared | Operating hours (hours (days) | Russian, Swedish, Turkish |
| Number of simultaneous touchpoints | 40 | Operating hours (hours/days) Mean time between failures (MTBF) | 16/7 50000 h |
| Multi-touch | Image: A set of the set of the | Power | |
| Native aspect ratio | 16:9 | Power consumption (standby) * | 0.5 W |
| Response time | 8 ms | Energy efficiency class (SDR) | G |
| Contrast ratio (typical) | 1200:1 | AC input voltage | 100 - 240 V |
| Viewing angle, horizontal | 178° | AC input frequency | 50 - 60 Hz |
| Viewing angle, vertical Display number of colours | 178° 1.07 billion colours | Computer system | |
| Pixel pitch | 0.372 x 0.372 mm | Computer system * | 1 |
| Display diagonal (metric) | 163.9 cm | Computer system type | System on Chip (SoC) |
| Ports & interfaces | | Built-in processor * | 1 |
| HDMI ports quantity * | 2 | Processor model | A55 |
| HDMI version | 2.0 | Internal memory | 4 GB |
| DVI port * | × | On-board graphics card model | ARM Mali-G52 |
| VGA (D-Sub) input ports | 1 | Internal storage capacity | 32 GB |
| USB port * | ✓ | Operating system installed | Android |
| USB ports quantity | 8 | Operating system version | 13 |
| USB connector type | USB Type-A, USB Type-C | Video formats supported | H.263, H.264, H.265, MPEG1, MPEG2, MPEG4, VP9 |
| USB 2.0 Type-B ports quantity | 3 | Audio formats supported | AAC, HE-AAC, MPEG |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity | 4 | Image formats supported | BMP, JPEG, PNG |
| USB 3.2 Gen 1 (3.1 Gen 1) Type-C | 1 | Weight & dimensions | |
| ports quantity | 1 | Display width | 1488 mm |
| USB Power Delivery (USB PD) | Image: A set of the set of the | Display depth | 87 mm |
| USB Power Delivery up to | 65 W | Display height | 896 mm |
| Ethernet LAN * | Image: A set of the set of the | Display weight | 35 kg |
| Ethernet LAN (RJ-45) ports | 2 | Packaging data | |
| RS-232C | Image: A set of the set of the | Package weight | 44.7 kg |
| Remote (IR) input | 1 | Packaging content | |
| Remote (IR) output | 1 | Remote control included | 1 |
| Card reader integrated | Image: A set of the set of the | | • |
| Compatible memory cards | MicroSD (TransFlash) | Batteries included | • |
| OPS module slot | Image: A second s | Stylus pen | × |
| | | Number of stylus pens | 1 |

| Audio | | Packaging content | |
|--|--|---|--|
| Built-in speaker(s) * Number of built-in speakers | | Cables included | AC, DVI, HDMI, IR sensor, RS-232, USB |
| RMS rated power | 32 W | Operational conditions | |
| Design | | Operating temperature (T-T) | 0 - 40 °C |
| Orientation Horizontal/Vertical | Digital signage flat panel Horizontal/Vertical Black | Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H) | 10 - 90% -20 - 60 °C 10 - 90% |
| Screen shape | Flat 600 x 400 mm | Certificates | |
| VESA mounting * Panel mounting interface | | Certification | CE, FCC, Class A, RoHS, CB, EAC, EMF, ETL |
| | | Technical details | |
| | | | 720 x 400 70Hz 832 x 624 75Hz |

 1440 x 900 60Hz 1600 x 900 60Hz

 1680 x 1050 60Hz 1920 x 1080

 60Hz 1024 x 768 60Hz 1152 x 870

 75Hz 1280 x 1024 60Hz 1280 x 720

 60Hz 3840 x 2160 30, 60Hz 640 x

480 60,67,75Hz 800 x 600 60Hz



8712581806064

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.