VERTIV.

Vertiv Avocent ACS8032MDAC-404 konsolipalvelin RJ-45

Tuotemerkki : Vertiv

Tuoteperhe: Avocent

Tuotekoodi: ACS8032MDAC-404

Tuotteen nimi : ACS8032MDAC-404

Vertiv Avocent ACS8032MDAC-404. Hallintaprotokolla: CLI, HTTP/ HTTPS, SNMP. Todennustapa: LOCAL,LDAP,RADIUS,TACACS+ and OneTimePasswords(OTP), Tietoturva-algoritmit: 3DES, 128-bit AES, 192-bit AES, 256-bit AES, AES, FIPS 140-2, HTTPS, IPSec, SHA-256, SNMP, SNMPv3,.... Console-portti: RJ-45, Pistorasian tyypit: C13 liitin. Käyttöjärjestelmä asennettu: Upotettu LINUX. Mitat (LxSxK): 438,2 x 241,3 x 44,5 mm, Paino: 3,4 kg



Technical details		Power	
Rack mounting Internal modem Zero Touch Provisioning (ZTP)	1 1 1	Power consumption (max) Input current Number of power supply units	35 W 0.1 A 2
Web-based management	1	Operational conditions	
Temperature sensor Product colour	✔ Black	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	-10 - 60 °C -20 - 70 °C 20 - 80%
Management features		Storage relative humidity (H-H)	20 - 80% 5 - 95%
Management protocols	CLI, HTTP/ HTTPS, SNMP	Certificates	
Security Authentication method Security algorithms	LOCAL,LDAP,RADIUS,TACACS+ and OneTimePasswords(OTP) 3DES, 128-bit AES, 192-bit AES, 256-bit AES, AES, FIPS 140-2, HTTPS, IPSec, SHA-256, SNMP, SNMPv3, SSH, SSH-2	Certification	FCC Class A, CE Class A (EU), ICES-003 (Canada), VCCI (Japan), RCM (Australia), Customs Union (CU), KCC (Korea), UL (USA), cUL (Canada), EN-60950 (EU), CB, Customs Union (CU)
		Memory	
IP address filtering One-time password (OTP)	4 4	Flash memory RAM capacity	16000 MB 1024 MB
Ports & interfaces		RAM type	DDR3L
Console port	RJ-45	eMMC capacity	16 GB
Serial ports quantity	32	Processor	
USB 2.0 ports quantity Ethernet LAN (RJ-45) ports SFP module slots quantity AC outlet types	8 2 2 C13 coupler	Processor family Processor architecture Processor cores Processor frequency	ARM Cortex-A9 ARM Cortex-A9 2 667 MHz
Software		Network	
Operating system installed	Embedded LINUX	Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Weight & dimensions Dimensions (WxDxH)	438.2 x 241.3 x 44.5 mm	Cable types supported	Cat5, Cat5e, Cat6, Cat6+, Cat6a, Cat6e, Cat7, Fiber
Weight	3.4 kg	Other features	
Power Power source type	AC	Safety	UL (USA), cUL (Canada), EN-60950 (EU), CB, Customs Union (CU)

Power

AC input voltage AC input frequency Power consumption (typical) 106 - 240 V 50 - 60 Hz 20 W





636430086293

0636430086293

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.