

Vertiv Avocent ACS808MEAC-404 konsolipalvelin RJ-45

Tuotemerkki : Vertiv

Tuoteperhe: Avocent

Tuotekoodi: ACS808MEAC-404



Tuotteen nimi :
ACS808MEAC-404

Vertiv Avocent ACS808MEAC-404. Hallintaprotokolla: CLI, HTTP/HTTPS, SNMP. Todennustapa: LOCAL, RADIUS, LDAP, TACACS+ and ONE TIME PASSWORD(OTP), Tietoturva-algoritmit: 3DES, 128-bit AES, 192-bit AES, 256-bit AES, FIPS 140-2, HTTPS, IPSec, SHA-256, SNMP, SNMPv3, SSH,... Console-portti: RJ-45. Käyttöjärjestelmä asennettu: Uputettu LINUX. Mitat (LxSxK): 212,6 x 181,9 x 29,5 mm, Paino: 1,09 kg

Technical details		Power	
Rack mounting	✓	DC input voltage	12 V
Internal modem	✓	Number of power supply units	1
Zero Touch Provisioning (ZTP)	✓	Operational conditions	
Web-based management	✓	Operating temperature (T-T)	0 - 70 °C
Temperature sensor	✓	Storage temperature (T-T)	-20 - 90 °C
Product colour	Black	Operating relative humidity (H-H)	20 - 80%
Event logging	✓	Storage relative humidity (H-H)	5 - 95%
Management features		Certificates	
Management protocols	CLI, HTTP/HTTPS, SNMP	Certification	FCC Class A, CE Class A (EU), ICES-003 (Canada), VCCI (Japan), RCM (Australia), Customs Union (CU), KCC (Korea)
Security		Memory	
Authentication method	LOCAL, RADIUS, LDAP, TACACS+ and ONE TIME PASSWORD(OTP)	Flash memory	16000 MB
Security algorithms	3DES, 128-bit AES, 192-bit AES, 256-bit AES, FIPS 140-2, HTTPS, IPSec, SHA-256, SNMP, SNMPv3, SSH, SSH-2	Card reader integrated	✗
IP address filtering	✓	RAM capacity	1024 MB
One-time password (OTP)	✓	RAM type	DDR3L
RSA SecurID	✓	eMMC capacity	16 GB
Ports & interfaces		Processor	
Console port	RJ-45	Processor family	ARM Cortex-A9
Serial ports quantity	8	Processor architecture	ARM Cortex-A9
USB 2.0 ports quantity	4	Processor cores	2
Ethernet LAN (RJ-45) ports	2	Processor frequency	667 MHz
Software		Network	
Operating system installed	Embedded LINUX	Copper ethernet cabling technology	10BASE-T, 100BASE-T, 1000BASE-T
Weight & dimensions		IP forwarding support	✓
Dimensions (WxDxH)	212.6 x 181.9 x 29.5 mm	Supported network protocols	IPv6
Weight	1.09 kg	Cable types supported	Cat5, Cat5e, Cat6, Cat6+, Cat6a, Cat6e, Cat7, Fiber
Power		Other features	
Power source type	AC, DC	Safety	UL (USA), cUL (CANADA), EN-60950 (EU), CB, Customs Union (CU)
AC input voltage	100 - 240 V		
AC input frequency	50 - 60 Hz		
Power consumption (typical)	7 W		
Power consumption (max)	28 W		



0636430087450



636430087450

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.