

## ATEN CL1016M KVM switch Rack mounting Black

Brand: ATEN Product code: CL1016M-ATA-2XK06SG

**Product name:** CL1016M

16 Port KVM with 17" LED-backlit LCD monitor

## ATEN CL1016M KVM switch Rack mounting Black:

The CL1016 LCD KVM Switch series are control units that allow access to multiple computers from a single keyboard, video, and mouse (KVM), console. A single CL1016 can control up to 16 computers. As many as 15 additional KVM switches can be daisy-chained to the CL1008, so that up to 256 computers can all be controlled from a single KVM console.

The CL1016 offers a space-saving, streamlined approach to KVM switch technology by integrating a keyboard, 17" LED-backlit LCD monitor, and touchpad in a 1U rack-mountable sliding housing. ATEN CL1016M. Maximum resolution: 1280 x 1024 pixels, Scan interval: 1,255 s. Product colour: Black, Rack capacity: 1U, Housing material: Metal, Plastic. Display: LCD, Display diagonal: 43.2 cm (17"). Input voltage: 100-240 V, AC input frequency: 50 - 60 Hz, Input current: 1 A. Width: 640.2 mm, Depth: 480 mm, Height: 44 mm

Ports & interfaces		Power	
Number of computers controlled *	16	AC input frequency	50 - 60 Hz
Performance		Input current	1 A
Maximum resolution *	1280 x 1024 pixels	Power consumption (typical)	20 W
Scan interval	1,255 s	System requirements	
DDC2B support	✓	Windows operating systems supported	<b>✓</b>
Hot-swap	✓	Linux operating systems supported	<b>✓</b>
Design		Operational conditions	
Rack capacity 1 Product colour * B	✓ 1U Black Metal, Plastic	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	0 - 50 °C -20 - 60 °C 0 - 80%
LED indicators	<b>✓</b>	Weight & dimensions	
Display		Width Depth	640.2 mm 480 mm
Built-in display *	<b>✓</b>	Height	44 mm
Display	LCD	Weight	13.6 kg
Display diagonal On Screen Display (OSD)	43.2 cm (17")	Packaging content	
Power	•	Manual	✓
Input voltage	100-240 V		

