



ATEN CL1000M KVM switch Rack mounting Black

Brand : ATEN

Product code: CL1000M-ATA-2XK06GG

Product name : CL1000M

17" LED-backlit LCD KVM Switch

[ATEN CL1000M KVM switch Rack mounting Black:](#)



The CL1000 is a LCD KVM console that serves as the front-end for standard KVM switches. The CL1000 features an integrated 17" LED-backlit LCD panel, full keyboard, and touchpad in a 1U, rack-mountable, Slideaway™ housing. Users who already have a switch can take advantage of the space saving and efficiency benefits of the CL1000 LCD KVM console without the unnecessary expense of having to purchase a KVM switch.

ATEN CL1000M. Maximum resolution: 1280 x 1024 pixels. Product colour: Black, Rack capacity: 1U, Housing material: Metal, Plastic. Display: LCD, Display diagonal: 43.2 cm (17"). Input voltage: 100-240 V, AC input frequency: 50 - 60 Hz, Input current: 1 A. Other operating systems supported: FreeBSD

| | | | |
|----------------------------------|--------------------|-------------------------------------|-------------|
| Ports & interfaces | | Power | |
| Number of computers controlled * | 1 | Power consumption (typical) | 16 W |
| Performance | | System requirements | |
| Maximum resolution * | 1280 x 1024 pixels | Windows operating systems supported | ✓ |
| DDC/DDC2 supported | ✓ | Linux operating systems supported | ✓ |
| DDC2B support | ✓ | Other operating systems supported | FreeBSD |
| Hot-swap | ✓ | Operational conditions | |
| Design | | Operating temperature (T-T) | 0 - 40 °C |
| Rack mounting * | ✓ | Storage temperature (T-T) | -20 - 60 °C |
| Rack capacity | 1U | Operating relative humidity (H-H) | 0 - 80% |
| Product colour * | Black | Weight & dimensions | |
| Housing material | Metal, Plastic | Width | 538.3 mm |
| LED indicators | ✓ | Depth | 480 mm |
| Display | | Height | 44 mm |
| Built-in display * | ✓ | Weight | 12 kg |
| Display | LCD | Packaging content | |
| Display diagonal | 43.2 cm (17") | Manual | ✓ |
| Power | | Logistics data | |
| Input voltage | 100-240 V | Harmonized System (HS) code | 85176200 |
| AC input frequency | 50 - 60 Hz | | |
| Input current | 1 A | | |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.